



Description:

20 AWG stranded (19x32) .037" tinned copper conductor, foam FEP insulation, Duobond® II (100% coverage) plus a tinned copper braid shield (93% coverage), fluorocopolymer jacket.

Usage (Overall)

Suitable Applications: Thin Ethernet

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	19x32	TC - Tinned Copper	.037

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FFEP - Foam Fluorinated Ethylene Propylene	.095

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	93

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVDF - Fluorocopolymer

Overall Cabling

Overall Nominal Diameter: 0.160 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +150°C

UL Temperature Rating: 150°C

Bulk Cable Weight: 25 lbs/1000 ft.

Max. Recommended Pulling Tension: 45 lbs.

Min. Bend Radius (Install)/Minor Axis: 1.800 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP, CL2P

CEC/C(UL) Specification: CMP

IEEE Specification: IEEE802.3 10Base2

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

89907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-01246-00
RG Type:	58AU

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9907

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
50	+/- 2

Nom. Inductance:

Inductance (µH/ft)
.0635

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
25.4

Nominal Velocity of Propagation:

VP (%)
80

Nominal Delay:

Delay (ns/ft)
1.27

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
8.8

Maximum Loop Resistance:

Resistance (Ohm/1000 ft)
15.24

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
5.8

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	.43
10	1.3
50	2.91
100	4.18

89907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

200	6.1
400	9.2
700	12.9
900	15.0
1000	16.0

Max. Power Rating:

Freq. (MHz)	Rating (W)
1	6450
2	4500
10	1850
20	1400
50	890
100	640
200	470
400	360
700	290
900	270
1000	260

Max. Operating Voltage - UL:

Voltage
300 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89907 E4X1000	1,000 FT	22.000 LB	GRAY, LIGHT DEC	C	#20 FPFA BRD SLF COAX
89907 E4X2500	2,500 FT	60.000 LB	GRAY, LIGHT DEC	C Z	#20 FPFA BRD SLF COAX
89907 E4X500	500 FT	11.000 LB	GRAY, LIGHT DEC	C	#20 FPFA BRD SLF COAX

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Computer and Instrumentation Cable

50 Ohm Ethernet® Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

Thinnet 10Base2 Ethernet • 20 AWG Stranded (19x32) .037" Conductor • Duobond® II + Overall TC Braid Shield (93% Coverage)

Non-plenum • Foam Polyethylene Insulation • Gray PVC Jacket

	UL AWM	9907	NEC:	500	152.4	12.5	5.7	20 AWG	.102	2.59	Duobond II*	.185	4.70	50	80%	25.4	83.3	1	.4	1.4	
	Style 1354		CL2	U-1000	U-304.8	24.0	10.9	(19x32)			+ 93%							10	1.3	4.3	
	(30V 60°C)		CM	1000	304.8	23.0	10.4	.037"			TC Braid							50	2.9	9.5	
			CEC:	1640	500.0	41.0	18.6	TC			5.8Ω/M'							100	4.2	13.8	
			CM	2500	762.0	62.5	28.4	8.8Ω/M'			19.0Ω/km								200	6.1	20.0
				3280	1000.0	82.0	37.3	28.9Ω/km											400	8.9	29.2

For Plenum versions see 89907 or 82907.

RG-58A/U Type
DEC Part No. 17-01248-00

Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket

	150°C	89907	NEC:	500	152.4	11.0	5.0	20 AWG	.095	2.41	Duobond II*	.160	4.06	50	80%	25.4	83.3	1	.4	1.4	
			CMP	1000†	304.8	22.0	10.0	(19x32)			+ 93%								10	1.3	4.3
			CL2P	2500†	762.0	60.0	27.3	.037"			TC Braid								50	2.9	9.5
			CEC:					TC			5.8Ω/M'								100	4.2	13.7
			CMP FT6					8.8Ω/M'			19.0Ω/km								200	6.1	20.0
								28.9Ω/km											400	9.2	30.2

For Non-plenum version see 9907.

RG-58A/U Type
DEC Part No. 17-01246-00. Suitable for Outdoor applications.

Plenum • FPFA Insulation • Natural Flamarrest® Jacket

	75°C	82907	NEC:	500†	152.4	11.0	5.0	20 AWG	.095	2.41	Duobond II*	.160	4.06	50	80%	25.4	83.3	1	.4	1.4	
			CMP	U-1000††	U-304.8	23.0	10.5	(19x32)			+ 93%								10	1.3	4.3
			CL2P	1000†	304.8	22.0	10.0	.037"			TC Braid								50	2.9	9.5
			CEC:	2500†	762.0	57.5	26.1	TC			5.8Ω/M'								100	4.2	13.7
			CMP FT6					8.8Ω/M'			19.0Ω/km								200	6.1	20.0
								28.9Ω/km											400	9.2	30.2

For Non-plenum version see 9907.

RG-58A/U Type

Thicknet 10Base5 Ethernet • 12 AWG Solid .086" Bare Copper Conductor • Duobond IV Quad Shield (100% Coverage)

Non-plenum • Foam Polyethylene Insulation • Yellow PVC Jacket

	UL AWM	9880	NEC:	500	152.4	66.0	30.0	12 AWG	.243	6.17	Duobond IV*	.405	10.29	50	78%	26.0	85.3	1	.2	.6	
	Style 1478		CL2	1000	304.8	131.0	59.5	(solid)			(Duobond II								5	.4	1.2
	(30V 60°C)		CM	1640	500.0	219.8	99.7	.086"			+ 94% TC Braid								10	.5	1.7
			CEC:					BC			+ Duofoil®								50	1.2	3.9
			CM					1.4Ω/M'			+ 90% TC Braid)								100	1.7	5.6
								4.7Ω/km			1.5Ω/M'								200	2.6	8.4

For Plenum version see 89880.

DEC Part No. 17-00451-00
Ring-band stripes marked every 2.5 meters to aid users in tap placement.

Plenum • Foam FEP Insulation • Orange Fluorocopolymer Jacket

	150°C	89880	NEC:	1000	304.8	134.0	60.9	12 AWG	.245	6.22	Duobond IV*	.375	9.53	50	78%	26.0	85.3	1	.2	.6	
			CL2P	1640†	500.0	224.7	102.1	(solid)			(Duobond II								5	.4	1.2
			CMP					.086"			+ 90% TC Braid								10	.5	1.7
			CEC:					BC			+ Duofoil								50	1.2	3.8
			CMP FT6					1.4Ω/M'			+ 90% TC Braid)								100	1.7	5.4
								4.7Ω/km			1.5Ω/M'								200	2.5	8.0

For Plenum version see 89880.

DEC Part No. 17-00324-00
Ring-band stripes marked every 2.5 meters to aid users in tap placement.
Suitable for Outdoor and Direct Burial applications.

BC = Bare Copper • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy • TC = Tinned Copper

*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).
Duobond IV = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).
†Final put-up length may vary from length shown ±10% for spools and reels, ±5% for UnReel® cartons.
††Length may vary -0/+10%.