



Description:

Low noise, RG-58/U Type, 22 AWG stranded (7x30) .030" TC conductor, polyethylene insulation, conductive layer, Duobond® II + TC braid shield (95% coverage), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	22	7x30	TC - Tinned Copper	.030

Insulation

Insulation Material:

Layer #	Insulation Material	Dia. (in.)
1	CPE - Conductive Polyethylene	0.036
2	PE - Polyethylene	0.112

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.195 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

Non-UL Temperature Rating: 80°C

Bulk Cable Weight: 23.800 lbs/1000 ft.

Max. Recommended Pulling Tension: 8.850 lbs.

Min. Bend Radius (Install)/Minor Axis: 2 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 58/U

Flame Test

UL Flame Test: UL1685 UL Loading, VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

50

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

37.0

Nominal Velocity of Propagation:

VP (%)

56

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

10.8

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

4.1

Other Electrical Characteristic 1: NBS Low Noise Test (Modified), MIL-C-17 Paragraph 4.8.14, 8 mV Peak to Peak Max

Max. Noise Level (Peak to Peak): 8 mV

Notes (Overall)

Notes: Not recommended for RF use

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9223 010100	100 FT	3.100 LB	BLACK		#22 LOW NOISE COAX CABLE
9223 0101000	1,000 FT	24.000 LB	BLACK	C	#22 LOW NOISE COAX CABLE
9223 010500	500 FT	12.000 LB	BLACK	C	#22LOW NOISE COAX CABLE

Notes:

C = CRATE REEL PUT-UP.

Special Audio, Communication and Instrumentation Cable

Miniature Instrumentation and Low Triboelectric Noise Coax

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

Miniature • 28 AWG Solid .013" Tinned Copper Conductor • Bare Copper Braid Shield (90% Coverage)

Polypropylene Insulation • Black PVC Jacket

105°C VW-1	8700	NEC: CMH CEC: CMH FT1	250	76.2	.8	.3	28 AWG (solid) .013" TC 66.9Ω/M' 219.5Ω/km	.023	.58	BC Braid 90% Shield Coverage 28.7Ω/M' 94.2Ω/km	.054	1.37	32	66%	55.2	181.1	1	2.5	8.2	7.7	25.3	17.2	56.4	24.5	80.4	34.8	114.2	50.0	164.4	66.0	216.5	75.0	246.1	79.0	259.2
---------------	-------------	--------------------------------	-----	------	----	----	--	------	-----	--	------	------	----	-----	------	-------	---	-----	-----	-----	------	------	------	------	------	------	-------	------	-------	------	-------	------	-------	------	-------



Low Noise • RG-174/U Type • 26 AWG Stranded (7x34) .019" Bare Copper-covered Steel Conductor • TC Braid Shield (90% Coverage)

Polyethylene Insulation • Conductive Layer • Black PVC Jacket

60°C	9239	—	100	30.5	1.0	.5	26 AWG (7x34) .019" BCCS 97.0Ω/M' 318.3Ω/km	.044	1.12	TC Braid 90% Shield Coverage 14.0Ω/M' 45.9Ω/km	.101	2.57	50	62%	38	125	—	—	—
			500	152.4	4.5	2.0													
			1000	304.8	8.0	3.6													

5mV peak-to-peak max.
Not recommended for RF use.

Low Noise • RG-59/U Type • 22 AWG Solid .025" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (93% Coverage)

Polyethylene Insulation • Conductive Layer • Black PVC Jacket

75°C VW-1	9224	—	U-500	U-152.4	19.5	8.9	22 AWG (solid) .025" BCCS 54.0Ω/M' 177.0Ω/km	.146	3.71	BC Braid 93% Shield Coverage 2.5Ω/M' 8.2Ω/km	.242	6.15	75	65%	22	72	—	—	—
			1000	304.8	39.0	17.7													

5mV peak-to-peak max.
Not recommended for RF use.

Low Noise • RG-58/U Type • 22 AWG Stranded (7x30) .030" TC Conductor • Duobond® II + TC Braid Shield (95% Coverage)

Polyethylene Insulation • Conductive Layer • Black PVC Jacket

80°C VW-1	9223	—	100	30.5	3.4	1.5	22 AWG (7x30) .030" TC 10.8Ω/M' 35.4Ω/km	.112	2.85	Duobond II* + 95% TC Braid 100% Shield Coverage 4.1Ω/M' 13.5Ω/km	.195	4.95	50	56%	37	122	—	—	—
			500	152.4	12.0	5.4													
			1000	304.8	24.0	10.9													

8mV peak-to-peak max.
Not recommended for RF use.

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • TC = Tinned Copper

*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).