



Description:

24 AWG stranded (7x32) tinned copper conductors, Datalene® insulation, twisted pairs, individually Beldfoil® shielded (100% coverage), 24 AWG stranded tinned copper drain wire, overall PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
4	24	7x32	TC - Tinned Copper	.024

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Datalene®	FPE - Foam Polyethylene	.061

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.363 in.

Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue

Pair Lay Length & Direction:

Lay Length (in.)	Twists/ft. (twist/ft)
1.750	6.850

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +80°C

UL Temperature Rating: 60°C (UL AWM Style 2493)

Bulk Cable Weight: 57 lbs/1000 ft.

9728 Multi-Conductor - Multi-Pair Snake Cable

Max. Recommended Pulling Tension:	65 lbs.
Min. Bend Radius (Install)/Minor Axis:	4 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2493 (300 V 60°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	89728

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
100

Nom. Inductance:

Inductance (µH/ft)
0.23

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
12.5

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
23.2

Nominal Velocity of Propagation:

VP (%)
76

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
24

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 15 Ohm/1000 ft

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
.384	0.74
.7056	0.87
.768	0.88
1.024	0.94

1.4112	1.01
1.536	1.03
2.048	1.13
2.8224	1.29
3.072	1.35
4.096	1.57
5.6448	1.78
6.144	1.84
8.192	2.13
11.2896	2.45
12.288	2.57
24.576	3.57

Max. Operating Voltage - UL:

Voltage
300 V RMS (UL AWM Style 2493)

Max. Recommended Current:

Current
2.5 Amps per conductor @ 25°C

Notes (Overall)

Notes: Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9728 060100	100 FT	6.000 LB	CHROME		4 FS PR #24 FHDPE PVC
9728 0601000	1,000 FT	51.000 LB	CHROME	C	4 FS PR #24 FHDPE PVC
9728 060500	500 FT	29.000 LB	CHROME		4 FS PR #24 FHDPE PVC

Notes:

C = CRATE REEL PUT-UP.

AES/EBU Digital Audio Cable

Multi-Pair Snake Cables
Individually Shielded Pairs

**Individually Shielded Pairs**

NEC: CM (CEC: CM)

Product Description

24 AWG stranded (7x32) tinned copper conductors. Datalene® insulation. Twisted pairs individually Beldfoil® shielded (100% Coverage). Overall Chrome PVC jacket and 24 AWG stranded tinned copper drain wire.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.


Color Code: See Chart 3 (in Technical Information Section)

Specifications

Nominal OD — Conductor	.024" (.60mm)
Nominal OD — Insulation	.061" (1.55mm)
Approvals	
NEC	CM
CEC	CM
UL Ratings	UL AWM Style 2493
Voltage Rating	300V
Temperature Rating	60°C
Non UL Temperature Rating	80°C
Nominal DCR	
Conductor	24.0Ω/M' (78.7Ω/km)
Shield	15.0Ω/M' (49.2Ω/km)
Nominal Impedance	100Ω
Nominal Velocity of Propagation	76%
Nominal Capacitance	
Between Conductors	12.5 pF/Ft. (41.0 pF/m)
Between Conductor/Shield*	23.2 pF/Ft. (76.1 pF/m)

DCR = DC Resistance

*Capacitance between one conductor and other conductors connected to shield.



Z-Fold®

Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Individually Shielded Pairs NEC: CM (CEC: CM)

24 AWG							
9729	2	100	30.5	4.3	2.0	.266	6.76
		500	152.4	20.5	9.3		
		1000	304.8	39.0	17.7		
		10000 [†]	3048.0	390.0	176.9		

For Plenum version of 9729, see 89729 or 82729.

9730	3	100	30.5	5.1	2.3	.334	8.48
		500	152.4	24.5	11.1		
		1000	304.8	46.0	20.9		
		10000 ^{††}	3048.0	520.0	236.4		

For Plenum version of 9730, see 89730.

9728	4	100	30.5	6.0	2.7	.363	9.22
		500	152.4	29.0	13.2		
		1000	304.8	51.0	23.1		

For Plenum version of 9728, see 89728.

9731	6	100	30.5	7.4	3.4	.421	10.69
		500	152.4	42.0	19.1		
		1000	304.8	83.0	37.7		

For Plenum version of 9731, see 89731.

9732	9	100	30.5	9.9	4.5	.488	12.40
		500	152.4	57.0	25.8		
		1000	304.8	106.0	48.1		

For Plenum version of 9732, see 89732.

9733	11	500	152.4	75.0	34.1	.575	14.61
9734	12	500	152.4	79.5	36.1	.575	14.61
		1000	304.8	154.0	70.0		

For Plenum version of 9734, see 89734.

9735	15	500	152.4	95.0	43.2	.639	16.23
		1000	304.8	185.0	84.1		

9736	17	500	152.4	103.5	47.0	.671	17.04
		1000	304.8	210.0	95.5		

9737	19	1000	304.8	231.0	105.0	.671	17.04
------	----	------	-------	-------	-------	------	-------

9738	27	1000	304.8	334.0	151.8	.797	20.24
------	----	------	-------	-------	-------	------	-------

[†] Total length may vary -10 to +5% from length shown and may contain 2 pieces. Minimum length of any one piece will be 1500 ft.

^{††} Total length may vary -10 to +20% from length shown and may contain 2 pieces. Minimum length of any one piece will be 1500 ft.