

9740 Multi-Conductor - Audio, Control and Instrumentation Cable



Description:

18 AWG stranded (16x30) tinned copper conductors, PVC insulation, twisted pairs, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.014

Inner Shield

Inner Shield Material:

Inner Shield Material
Unshielded

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.032

Overall Cabling

Overall Nominal Diameter: 0.210 in.

Pair

Pair Color Code Chart:

Number	Color
1	Black & Red

Pair Lay Length & Direction:

Lay Length (in.)	Twists/ft. (twist/ft)
2.000	6.000

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +80°C
Non-UL Temperature Rating:	80°C (UL AWM Style 2464)
Bulk Cable Weight:	22.400 lbs/1000 ft.
Max. Recommended Pulling Tension:	45 lbs.
Min. Bend Radius (Install)/Minor Axis:	2.250 in.

9740 Multi-Conductor - Audio, Control and Instrumentation Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
AWM Specification:	UL Style 2464 (300 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

C(UL) Flame Test:	FT4
-------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	89740, 87740, 82740

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

25.5

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.86

Max. Operating Voltage - UL:

Voltage

300 V RMS (UL AWM Style 2464)

Max. Recommended Current:

Current

4.8 Amps per conductor @ 20°C

Put Ups and Colors:


Item #	Putup	Ship Weight	Color	Notes	Item Desc
9740 060U1000	1,000 FT	24.000 LB	CHROME		2 #18 PVC FRPVC
9740 060U500	500 FT	12.500 LB	CHROME		2 #18 PVC FRPVC
9740 0601000	1,000 FT	24.000 LB	CHROME	C	2 #18 PVC FRPVC
9740 060500	500 FT	12.500 LB	CHROME	C	2 #18 PVC FRPVC

Notes:

C = CRATE REEL PUT-UP.

Unshielded

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	
18 AWG Stranded (16x30) Tinned Copper Conductors • Twisted Pairs															
PVC Insulation • Chrome PVC Jacket															
	9740	NEC: CMG CEC: CMG FT4	1	See Chart 3 (Tech Info Section)	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	12.5 12.5 24.0 24.0	5.7 5.7 10.9 10.9	.014	.36	.032	.81	.210	5.33	
															For Plenum versions of 9740, see 89740, 87740 or 82740.
	9156	NEC: CMG CEC: CMG FT4	2	See Chart 3 (Tech Info Section)	U-500 500 U-1000 1000	U-152.4 152.4 U-304.8 304.8	25.0 27.0 49.0 51.0	11.3 12.2 22.2 23.2	.014	.36	.035	.89	.333	8.46	
	8690	NEC: CMG CEC: CMG FT4	3	See Chart 3 (Tech Info Section)	100 U-500 500 1000	30.5 U-152.4 152.4 304.8	7.0 32.5 34.0 65.0	3.2 14.8 15.4 29.5	.014	.36	.032	.81	.347	8.81	
	9157	NEC: CMG CEC: CMG FT4	4	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.4 41.0 83.0	3.8 18.6 37.7	.014	.36	.032	.81	.381	9.68	
	9159	NEC: CMG CEC: CMG FT4	5	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	50.0 99.0	22.7 45.0	.014	.36	.032	.81	.391	9.93	
	8691	NEC: CMG CEC: CMG FT4	6	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	58.0 115.0	26.4 52.3	.014	.36	.032	.81	.433	11.00	
	9161	NEC: CMG CEC: CMG FT4	8	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	14.2 78.0 152.0	6.4 35.6 69.3	.014	.36	.037	.94	.485	12.32	
	8692	NEC: CMG CEC: CMG FT4	9	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	87.0 170.0	39.5 77.3	.014	.36	.040	1.02	.524	13.31	
	9741	NEC: CMG CEC: CMG FT4	12	See Chart 3 (Tech Info Section)	100 1000	30.5 304.8	25.4 220.0	11.5 99.8	.014	.36	.046	1.17	.600	15.24	
	9742	NEC: CMG CEC: CMG FT4	15	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	30.9 146.5 291.0	14.0 66.5 132.0	.014	.36	.051	1.30	.677	17.20	
	9743	NEC: CMG CEC: CMG FT4	19	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	37.0 179.0 355.0	16.8 81.4 161.4	.014	.36	.055	1.40	.721	18.31	