

9975 Hook-up/Lead - UL AWM Style 1061

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	24
Stranding	Solid
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.010 in.

OVERALL:

Overall Nominal Diameter	.040 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	1061
UL Rating	300 V RMS, 80°C
CSA Type	AWM I, A/B
CSA Rating	300 V RMS, 80°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

FLAME TEST:

UL Flame Test	VW-1
CSA Flame Test	FT1

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

9975 Hook-up/Lead - UL AWM Style 1061

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9975 001100	24 SOL PVC BRN	100	0.2	BROWN	
9975 0011000	24 SOL PVC BRN	1000	2	BROWN	P
9975 002100	24 SOL PVC RED	100	0.2	RED	
9975 0021000	24 SOL PVC RED	1000	2	RED	P
9975 0025000	#24 SOL PVC RED	5000	10	RED	P
9975 0031000	24 SOL PVC ORG	1000	2	ORANGE	P
9975 004100	24 SOL PVC YEL	100	0.2	YELLOW	
9975 0041000	24 SOL PVC YEL	1000	2	YELLOW	P
9975 005100	24 SOL PVC GRN	100	0.2	GREEN, DARK	
9975 0051000	24 SOL PVC GRN	1000	2	GREEN, DARK	P
9975 007100	24 SOL PVC VIO	100	0.2	VIOLET	
9975 0071000	24 SOL PVC VIO	1000	2	VIOLET	P
9975 0081000	24 SOL PVC GRY	1000	2	GRAY	P
9975 009100	24 SOL PVC WHT	100	0.2	WHITE	
9975 0091000	24 SOL PVC WHT	1000	2	WHITE	P
9975 010100	24 SOL PVC BLK	100	0.2	BLACK	
9975 0101000	24 SOL PVC BLK	1000	2	BLACK	P
9975 0105000	#24 SOL PVC BLK	5000	10	BLACK	P
9975 013100	24 SOL PVC DK.BLU	100	0.2	BLUE, DARK	
9975 0131000	24 SOL PVC DK.BLU	1000	2	BLUE, DARK	P

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 11-17-2006

9975 Hook-up/Lead - UL AWM Style 1061

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.