

9982 Hook-up/Lead - UL AWM Style 1061

| | |
|--|---|
|  | <p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> |
|--|---|

Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

| | |
|----------------------------|--------------------|
| Number of Conductors | 1 |
| Total Number of Conductors | 1 |
| AWG | 20 |
| Stranding | 7x28 |
| Conductor Material | TC - Tinned Copper |

INSULATION:

| | |
|----------------------|--------------------------|
| Insulation Material | PVC - Polyvinyl Chloride |
| Insulation Thickness | .010 in. |

OVERALL:

| | |
|--------------------------|----------|
| Overall Nominal Diameter | .057 in. |
|--------------------------|----------|

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

| | |
|---------------------------------------|-----------------|
| UL AWM Style | 1061 |
| UL Rating | 300 V RMS, 80°C |
| CSA Type | AWM I, A/B |
| CSA Rating | 300 V RMS, 80°C |
| EU CE Mark (Y/N) | Yes |
| EU RoHS Compliant (Y/N) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |

FLAME TEST:

| | |
|----------------|------|
| UL Flame Test | VW-1 |
| CSA Flame Test | FT1 |

PLENUM/NON-PLENUM:

| | |
|--------------|---|
| Plenum (Y/N) | N |
|--------------|---|

9982 Hook-up/Lead - UL AWM Style 1061

PUT-UPS AND COLORS:

| Item | Description | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|---------------|-------------------|--------------|--------------------|--------------|-------|
| 9982 001100 | 20 STR PVC BRN | 100 | 0.4 | BROWN | |
| 9982 0011000 | 20 STR PVC BRN | 1000 | 5 | BROWN | P |
| 9982 002100 | 20 STR PVC RED | 100 | 0.4 | RED | |
| 9982 0021000 | 20 STR PVC RED | 1000 | 5 | RED | P |
| 9982 003100 | 20 STR PVC ORG | 100 | 0.4 | ORANGE | |
| 9982 0031000 | 20 STR PVC ORG | 1000 | 5 | ORANGE | P |
| 9982 004100 | 20 STR PVC YEL | 100 | 0.4 | YELLOW | |
| 9982 0041000 | 20 STR PVC YEL | 1000 | 5 | YELLOW | P |
| 9982 005100 | 20 STR PVC DK.GRN | 100 | 0.4 | GREEN, DARK | |
| 9982 0051000 | 20 STR PVC DK.GRN | 1000 | 5 | GREEN, DARK | P |
| 9982 0071000 | 20 STR PVC VIO | 1000 | 5 | VIOLET | P |
| 9982 0081000 | 20 STR PVC GRY | 1000 | 5 | GRAY | P |
| 9982 009100 | 20 STR PVC WHT | 100 | 0.4 | WHITE | |
| 9982 0091000 | 20 STR PVC WHT | 1000 | 5 | WHITE | P |
| 9982 0095000 | 20 STR PVC WHT | 5000 | 20 | WHITE | P |
| 9982 009D5000 | 20 STR PVC WHT | D5000 | 25 | WHITE | |
| 9982 010100 | 20 STR PVC BLK | 100 | 0.4 | BLACK | |
| 9982 0101000 | 20 STR PVC BLK | 1000 | 5 | BLACK | P |
| 9982 013100 | 20 STR PVC DK.BLU | 100 | 0.4 | BLUE, DARK | |
| 9982 0131000 | 20 STR PVC DK.BLU | 1000 | 5 | BLUE, DARK | P |

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 11-17-2006

9982 Hook-up/Lead - UL AWM Style 1061

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.