

## 9983 Hook-up/Lead - UL AWM Style 1061

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

### Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	22
Stranding	7x30
Conductor Material	TC - Tinned Copper

#### INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.010 in.

#### OVERALL:

Overall Nominal Diameter	.050 in.
--------------------------	----------

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

UL AWM Style	1061
UL Rating	300 V RMS, 80°C
CSA Type	AWM I, A/B
CSA Rating	300 V RMS, 80°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

#### FLAME TEST:

UL Flame Test	VW-1
CSA Flame Test	FT1

#### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

**9983 Hook-up/Lead - UL AWM Style 1061**

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9983 001100	22 STR PVC BRN	100	0.3	BROWN	
9983 0011000	22 STR PVC BRN	1000	4	BROWN	P
9983 001D1000	22 STR PVC BRN	D1000	4	BROWN	
9983 001D5000	22 STR PVC BRN	D5000	15	BROWN	
9983 002100	22 STR PVC RED	100	0.3	RED	
9983 0021000	22 STR PVC RED	1000	4	RED	P
9983 002D1000	22 STR PVC RED	D1000	4	RED	
9983 002D5000	22 STR PVC RED	D5000	15	RED	
9983 003100	22 STR PVC ORG	100	0.3	ORANGE	
9983 0031000	22 STR PVC ORG	1000	4	ORANGE	P
9983 003D1000	22 STR PVC ORG	D1000	4	ORANGE	
9983 003D5000	22 STR PVC ORG	D5000	15	ORANGE	
9983 004100	22 STR PVC YEL	100	0.3	YELLOW	
9983 0041000	22 STR PVC YEL	1000	4	YELLOW	P
9983 004D1000	22 STR PVC YEL	D1000	4	YELLOW	
9983 004D5000	22 STR PVC YEL	D5000	15	YELLOW	
9983 005100	22 STR PVC GRN	100	0.3	GREEN, DARK	
9983 0051000	22 STR PVC GRN	1000	4	GREEN, DARK	P
9983 005D1000	22 STR PVC DGRN	D1000	4	GREEN, DARK	
9983 005D5000	22 STR PVC DGRN	D5000	15	GREEN, DARK	
9983 007100	22 STR PVC VIO	100	0.3	VIOLET	
9983 0071000	22 STR PVC VIO	1000	4	VIOLET	P
9983 007D1000	22 STR PVC VIO	D1000	4	VIOLET	
9983 007D5000	22 STR PVC VIO	D5000	15	VIOLET	
9983 008100	22 STR PVC GRY	100	0.3	GRAY	
9983 0081000	22 STR PVC GRY	1000	4	GRAY	P

**9983 Hook-up/Lead - UL AWM Style 1061**

9983 008D1000	22 STR PVC GRY	D1000	4	GRAY	
9983 008D5000	22 STR PVC GRY	D5000	15	GRAY	
9983 009100	22 STR PVC WHT	100	0.3	WHITE	
9983 0091000	22 STR PVC WHT	1000	4	WHITE	C P
9983 0095000	#22 STR PVC WHT	5000	15	WHITE	P
9983 009D1000	22 STR PVC WHT	D1000	4	WHITE	
9983 009D21	22 STR PVC WHT	D21	0.063	WHITE	
9983 009D5000	22 STR PVC WHT	D5000	15	WHITE	
9983 010100	22 STR PVC BLK	100	0.3	BLACK	
9983 0101000	22 STR PVC BLK	1000	4	BLACK	P
9983 01010000	#22 STR PVC BLK	10000	30	BLACK	P
9983 010D1000	22 STR PVC BLK	D1000	4	BLACK	
9983 010D21	22 STR PVC BLK	D21	0.063	BLACK	
9983 010D5000	22 STR PVC BLK	D5000	15	BLACK	
9983 010M1000	22 STR PVC BLK	M1000	4	BLACK	
9983 013100	22 STR PVC DK.BLU	100	0.3	BLUE, DARK	
9983 0131000	22 STR PVC DK.BLU	1000	4	BLUE, DARK	P
9983 013D1000	22 STR PVC DBLU	D1000	4	BLUE, DARK	
9983 013D5000	22 STR PVC DBLU	D5000	15	BLUE, DARK	

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1      Revision Date: 11-17-2006

---

## 9983 Hook-up/Lead - UL AWM Style 1061

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.