

9986 Hook-up/Lead - UL AWM Style 1061



Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1				
Total Number of Conductors	1				
AWG	28				
Stranding	7x36				
Conductor Material	TC - Tinned Copper				
INSULATION:					
Insulation Material	PVC - Polyvinyl Chloride				
Insulation Thickness	.010 in.				
OVERALL:					
Overall Nominal Diameter	.035 in.				
APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:					
APPLICABLE STANDARDS:					
UL AWM Style	1061				
UL Rating	300 V RMS, 80°C				
CSA Type	AWM I, A/B				
CSA Rating	300 V RMS, 80°C				
EU CE Mark (Y/N)	Yes				
EU RoHS Compliant (Y/N)	Yes				
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005				
FLAME TEST:					
UL Flame Test	VW-1				
PLENUM/NON-PLENUM:					
Plenum (Y/N)	Ν				

PUT-UPS AND COLORS:



9986 Hook-up/Lead - UL AWM Style 1061

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9986 001100	28 STR PVC BRN	100	0.1	BROWN	
9986 0011000	28 STR PVC BRN	1000	2	BROWN	Р
9986 002100	28 STR PVC RED	100	0.1	RED	
9986 0021000	28 STR PVC RED	1000	2	RED	Р
9986 003100	28 STR PVC ORG	100	0.1	ORANGE	
9986 0031000	28 STR PVC ORG	1000	2	ORANGE	Р
9986 004100	28 STR PVC YEL	100	0.1	YELLOW	
9986 0041000	28 STR PVC YEL	1000	2	YELLOW	Р
9986 005100	28 STR PVC GRN	100	0.1	GREEN, DARK	
9986 0051000	28 STR PVC GRN	1000	2	GREEN, DARK	Р
9986 007100	#28 STR PVC VIO	100	0.1	VIOLET	
9986 0071000	#28 STR PVC VIO	1000	2	VIOLET	Р
9986 008100	28 STR PVC GRY	100	0.1	GRAY	
9986 0081000	28 STR PVC GRY	1000	2	GRAY	P
9986 009100	28 STR PVC WHT	100	0.1	WHITE	
9986 0091000	28 STR PVC WHT	1000	2	WHITE	P
9986 010100	28 STR PVC BLK	100	0.1	BLACK	
9986 0101000	28 STR PVC BLK	1000	2	BLACK	P
9986 013100	28 STR PVC DK.BLU	100	0.1	BLUE, DARK	
9986 0131000	28 STR PVC DK.BLU	1000	2	BLUE, DARK	Р

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 11-17-2006

Detailed Specifications & Technical Data



9986 Hook-up/Lead - UL AWM Style 1061

© Copyright 2006 Belden, Inc All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & California Proposition 65 Consent Judgment For Wire & California Proposition 65 Consent Judgment 2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.