

9995 Multi-Conductor - Audio, Control and Instrumentation Cable



Description:

24 AWG stranded (7x32) TC conductors, polyethylene insulation, twisted pairs, individually shielded w/Beldfoil® (100% coverage), 24 AWG stranded TC drain wire, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
25	24	7x32	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material
PE - Polyethylene

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: Stranded

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.636 in.

Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue
11	Red & Yellow
12	Red & Brown
13	Red & Orange
14	Green & White

9995 Multi-Conductor - Audio, Control and Instrumentation Cable

15	Green & Blue
16	Green & Yellow
17	Green & Brown
18	Green & Orange
19	White & Blue
20	White & Yellow
21	White & Brown
22	White & Orange
23	Blue & Yellow
24	Blue & Brown
25	Blue & Orange

Pair Lay Length & Direction:

Lay Length (in.)
1.750

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +80°C
UL Temperature Rating:	80°C (UL AWM Style 2919)
Bulk Cable Weight:	724 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	6.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2919 (30 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
-----------------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
----------------------	----

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
60

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
25

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
47

Nominal Velocity of Propagation:

9995 Multi-Conductor - Audio, Control and Instrumentation Cable

VP (%)

66

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

24

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 18 Ohm/1000 ft

Max. Operating Voltage - UL:

Voltage

30 V RMS (UL AWM Style 2919)

300 V RMS

Max. Recommended Current:

Current

1.1 Amps per conductor @ 25°C (10°C rise in temp)

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9995 0601000	1,000 FT	228.000 LB	CHROME	C	25 FS PR #24 PE PVC
9995 060500	500 FT	116.000 LB	CHROME	C	25 FS PR #24 PE PVC

Notes:

C = CRATE REEL PUT-UP.

Introduction

Belden® paired cable products are manufactured in a variety of gage sizes, dimensions, insulation materials, shielding configurations, and jacketing materials including Plenum and High-Temperature versions to meet the technical requirements of many different types of systems.

Paired cables allow balanced signal transmission, which results in lower crosstalk through common mode rejection. Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables.

As an aid to proper cable selection, both the suggested working voltages and the maximum temperature ratings are indicated for each applicable paired cable selection.


Most of our paired cables are available from stock. Many of these are available off the shelf from distributors. If you have a new or unusual application or you cannot find a paired cable in this catalog section that meets your technical requirements, contact Technical Support at 1-800-BELDEN-1.


Paired Cables Packaging

Belden's unique UnReel® cable dispenser is available for many of the paired cable products listed in this section. The letter "U" before the specified put-up length denotes UnReel packaging.

Individually Shielded

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. of Prop. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Polyethylene Insulation • Chrome PVC Jacket																		
 <p>UL AWM Style 2919 (30V 80°C)</p> <p>Z-Fold®</p>	9990	NEC: CM CEC: CM	3	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	16.0 36.0	7.3 16.4	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.255 6.48	60	66%	25	82	47	154	
	9991	NEC: CM CEC: CM	6	See Chart 3 (Tech Info Section)	500 1000	30.5 304.8	6.7 62.0	3.1 28.3	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.330 8.38	60	66%	25	82	47	154	
	9992	NEC: CM CEC: CM	9	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.8 42.5 86.0	4.0 19.3 39.1	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.383 9.73	60	66%	25	82	47	154	
	9993	NEC: CM CEC: CM	12	See Chart 3 (Tech Info Section)	100 1000	30.5 304.8	9.8 107.0	4.5 48.6	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.428 10.87	60	66%	25	82	47	154	
	9995	NEC: CM CEC: CM	25	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	21.2 116.0 228.0	9.7 52.7 103.6	24.0Ω/M' 78.7Ω/km	18.0Ω/M' 59.1Ω/km	.636 16.15	60	66%	25	82	47	154	

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
22 AWG Solid Conductors • TC • Twisted Pairs • Individually Shielded w/ Beldfoil (100% Coverage) • 22 AWG Solid TC Drain Wire																		
PVC Insulation • Overall Chrome PVC Jacket																		
 <p>UL AWM Style 2464 (300V 80°C)</p> <p>Z-Fold®</p>	8767	NEC: MPG, CMG CEC: MPG, CMG FT4	3	See Chart 3 (Tech Info Section)	U-500 500 1000	U-152.4 152.4 304.8	22.5 23.0 46.0	10.3 10.5 21.0	.013 .013 .013	.33 .33 .33	.037 .037 .040	.94 .94 1.02	.279 .379 .425	7.10	40	131	77	253
	8768	NEC: MPG, CMG CEC: MPG, CMG FT4	6	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	46.5 92.0	21.1 41.8	.013 .013	.33 .33	.037 .037	.94 .94	.379 9.60	40	131	77	253	
	8764	NEC MPG, CMG CEC: MPG, CMG FT4	9	See Chart 3 (Tech Info Section)	1000	304.8	122.0	55.5	.013	.33	.040	1.02	.425	10.80	40	131	77	253
	8765	NEC MPG, CMG CEC: MPG, CMG FT4	11	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	76.5 149.0	34.8 67.7	.013 .013	.33 .33	.040 .040	1.02 1.02	.470 11.90	40	131	77	253	
	8766	NEC: MPG, CMG CEC: MPG, CMG FT4	15	See Chart 3 (Tech Info Section)	500 1000	152.4 304.8	101.5 196.0	46.1 89.1	.013 .013	.33 .33	.045 1.14	1.14	.525	13.30	40	131	77	253

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.