Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX102900 Panels - KeyConnect Modular Furniture Adapter, 4 Port







For more Information please call

1-800-Belden1



Description:

KeyConnect Modular Furniture Adapter, 4 Port

Usage	(Overall)
	•

Suitable Applications: - Compatible with a variety of modules that are suitable for use with Belden

IBDN Systems 10GX, 4800,3600, 2400 and 1200.

Related Parts: - Compatible with 10GX, CAT6+ and CAT5E KeyConnect UTP and Multimedia

Modules

Physical Characteristics (Connectivity)

Capacity

Max. Capacity: 4 inserts

Access

Front Connection: Flush

Dimensions

Dimensions:

 Height (in.)
 Width (in.)
 Depth (in.)

 1.840
 3.130
 0.190

Materials

Materials:

Description	Material	
Modular Furniture Adapter	Plastic - UL94V-0	

Color

Color: Elec. White

Weight

Weight: 0.040 lbs.

Included Parts

Included Parts: installation sheet, blank

Packaging

Packaging: Individually packaged in a plastic bag

Mechanical Characteristics (Connectivity)

Footprint/Type: KeyConnect

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006

MII Order #39 (China RoHS): Yes

Page 1 of 2 03-12-2010

Detailed Specifications & Technical Data





AX102900 Panels - KeyConnect Modular Furniture Adapter, 4 Port

Safety Listing: Bi-national (UL/CSA) Standard Listed Suitability Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Transmission Specifications:

Notes (Overall)

Notes: For proper installation refer to installation guide included with the product or visit our web site at http://www.belden.com

Product Family

Part Numbers:

Description	Almond	Elec. White	Black
KeyConnect Modular Furniture Adapter 3 Ports	AX103925	AX102991	AX102992
KeyConnect Modular Furniture Adapter 4 Ports	AX103926	AX102900	AX102901

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc

Revision Number: 0 Revision Date: 06-05-2009

© 2010 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.