

January 13, 2006

Products

Accessories

New Products

Where to Buy

Service / Repair

Dist. Access

Online Tools

Warranty Reg.

Download

Application Notes

International

Join Our
Newsletter

E-Mail Address:

First Name:

Last Name:

Subscribe

Unsubscribe

RIGHT ANGLE CARD EDGE CONNECTOR

Model#205

RAA

|

Banana Plug Adapter Set

Model#AD 101 - 1 red and 1 black 4mm Banana Plugs - 42V (1000V) 36A Rating with trained user

|

INSULATED BNC-4mm SAFETY JACK

Model#AD 110 Fully Insulated BNC male to 4mm sheathed Jack. Use DMM test leads on BNC female connectors.

- IEC61010-1 500V CAT 1
- 50 impedance
- Fully Insulated

|

TELESCOPING ANTENNA, BNC CONNECTOR

Model#AT 20

|

RIGHT ANGLE TELESCOPING ANTENNA, BNC CONNECTOR

Model#AT 21

|

AC ADAPTER, 9VDC/300mA, Center -

Model#BE 11

- UL & CSA Listed
- Barrel Jack Dimensions: 12mm long, 5mm diameter, 2mm internal diameter

|

205 CABLE TESTER, REPLACEMENT PCB

Model#205 PCB

|

POWER ADAPTER, 9V DC 100mA, Center -

Model#BE 9

- UL & cUL Listed
- Barrel Jack Dimensions: 11mm long, 3mm diameter, 1mm internal diameter

|

BNC to BNC, RG58C/U, 36inch

Model#CC-41A

- Standard BNC Cable assembly
- Molded strain relief boot
 - RG58C/U cable and 50 ohm impedance
 - 500Vrms voltage rating
 - 40" cable length

\$10.00

| [Datasheet](#) | [Features](#) |

LEAD SET, Shth P-RtP, SILICONE, 1.5m

Model#CC 104

- Highly Flexible Silicone Jacket
- 4mm Sheathed Straight to Right-Angle Plugs
- 60" (1.5m) length
- IEC61010 1000V CATIII 12A Rating

|

INSULATED BNC-BNC CABLE BLACK

Model#CC 110

Standard BNC cable assembly with a molded strain release boots provides for long-life. RG58C/U cable and 50 ohm impedance. CC-110 is a special fully insulated BNC male to male cable assembly. Meets IEC61010 safety standards.

[| Features |](#)

BNC STACKABLE SHEATHED PLUG LD

Model#CC 130 - Fully insulated BNC male to Sheathed Stacking 4mm plugs - Meets IEC61010 safety standards - Includes highly flexible RG58 Type cable in a 2.0 meter length

[| Features |](#)

BNC to BNC, RG/58U, 60inch

Model#CC-150 - Fully insulated BNC male to BNC male - Meets IEC61010 safety standards - Includes highly flexible RG58C/U type cable in a 48" (1.2m) length

[| Datasheet | Features |](#)

BNC Breakout to Alligator Clips

Model#CC-21 Standard BNC to Alligator clips test leads.

- 50 ohm impedance
- RG58C/u cable
- 500Vrms voltage rating
- 40" cable length

BNC / N Adapter Kit

- Model#CC-25** This kit contains the most popular In Series and Between Series BNC and N type adapters. Solve your hookup problems easily. Bodies are brass, nickel plated with gold plated center contacts.
- Nine BNC and N type adapters
 - 50 ohm impedance
 - 500Vrms Rating

[| Specs](#) | [Features](#) |

AC ADAPTER, 9VDC/300mA, Center +

- Model#BE 12**
- UL & CSA Listed
 - Barrel Jack Dimensions: 12mm long, 5mm diameter, 2mm internal diameter

Note: If you can't find the part number you're searching for then it might be an obsolete model. Try to search for it under [Service/Repair](#) section.

[Home](#) | [About B+K](#) | [Contact Us](#) | [Press Releases](#) | [F.A.Q.](#) | [Sitemap](#)

B&K Precision Corporation
22820 Savi Ranch Parkway
Yorba Linda, CA 92887 U.S.A.
Phone: (714) 921-9095, Fax: (714) 921-6422

[Switching Power Supply](#), [Function Generator](#), [Arbitrary Waveform Generator](#)
[Anemometer](#), [Hygrometer](#), [Programmer](#), [Multimeter](#), [Analog Oscilloscope](#), [Spectrum Analyzer](#)
[Lcr / Esr meter](#), [Capacitance Meter](#), [Volt Meter](#), [Current Clamp Meter](#), [Ph Meter](#), [Humidity Meter](#)