

Diecast Aluminum Enclosures - With Bottom Flange Light Duty Watertight (1590W_F Series)

Home

Products

Distributors

Technical

Contact Us

Other Options

Path: Home > Enclosure Index > Diecast Aluminum - Light Duty Watertight (With Bottom Flange)







click to enlarge

click to enlarge

click to enlarge

Key Features:

- Rugged, diecast aluminum alloy (tough yet easy to machine), electronic instrument enclosure.
- Lid screws are exposed for easy enclosure access (if you require higher security see our watertight flanged lid version).
- Bottom flange is an aluminum plate, welded onto the base of the enclosure.
- Lap joint construction with a factory poured silicone rubber gasket around the perimeter of the lid provides protection against access of dust and water.
- Silicone rubber gasket remains flexible from -62 to +232°C (-80 to +450 °F).
- Unpainted version is vibra finished for a smooth surface with no sharp edges.
- Painted version is painted with tough polyester powder paint for a lasting finish, even after machining. Paint is only applied to the exterior surface. Black screws are included to enhance appearance.
- Four (or 6 in 1590D, 1590DD & 1590E, 8 in 1590F) 6-32 x 1/2" stainless steel machine screws secure lid into factory tapped holes.
- Screws use neoprene "O" rings (included).
- Designed to meet IP65.
- Low side wall draft angle (2 degrees or less) for easy P.C. board mounting.
- Link here to photo tables of each part number note: regular, unflanged version shown for sizing

Part Number	Color	Reader File	Drawing File Size	AutoCAD .dwg File (zipped)	.zip File Size	Units	Length	Width	Enclosure Depth (Less Lid)
1590WLLBF	Unpainted	PDF	133K	33K ZIP	185K	Inches	1.97	1.97	0.83
590WLLBFBK	Black	P	1331			mm	50	50	21
1590WLBF	Unpainted Black	PDF	141K	ZIP	172K	Inches	1.99	1.99	1.06
1590WLBFBK						mm	51	51	27
1590WHF	Unpainted Black	POF J	145K	ZIP	273K	Inches	2.07	1.5	1.06
1590WHFBK						mm	52.5	38	27
1590WYF	Unpainted	PDF	121K	ZIP	177K	Inches	3.62	3.62	1.50
1590WYFBK	Black	Po	12111		1//1	mm	92	92	38
1590WAF	Unpainted Black	₽DF }	129K	ZIP	155K	Inches	3.64	1.52	1.06
1590WAFBK						mm	93	39	27
1590WGF 1590WGFBK	Unpainted Black	EUF.	136K	ZIP	263K	Inches	3.94	1.97	0.83
						mm	100	50	21
1590WSF 1590WSFBK	Unpainted Black	PDF	135K	ZIP	227K	Inches	4.35	3.21	1.57
						mm	111	82	40
1590WBF 1590WBFBK	Unpainted Black	₽0₽ }	128K	ZIP	174K	Inches	4.39	2.34	1.06
						mm	112	60	27
1590WBBF 1590WBBFBK	Unpainted Black	POF A	166K	ZIP	177K	Inches	4.67	3.68	1.18
						mm	119	94	30
1590WQF 1590WQFBK	Unpainted Black	PUF	132K	ZIP	427K	Inches	4.70	4.70	1.1
						mm	120	120	28
1590WUF 1590WUFBK	Unpainted Black	F	124K	ZIP	268K	Inches	4.70	4.70	2.17
						mm	120	120	55
1590WVF	Unpainted	PDF	118K	ZIP	238K	Inches	4.70	4.70	3.54
1590WVFBK	Black	P				mm	120	120	90
1590WCF 1590WCFBK	Unpainted Black	₽DF }	128K	ZIP	288K	Inches	4.72	3.70	2.07
						mm	120	94	53

1590WTF	TT : . 1	lear I				Inches	4.74	3.13	2.17
590W 1F 590WTFBK	Unpainted Black	₽DE	133K	ZIP	211K	mm	121	80	55
1590WN1F 1590WN1FBK	Unpainted Black		125K	ZIP	244K	Inches	4.77	2.6	1.39
						mm	121.1	66	35.3
1590WKKF 1590WKKFBK	Unpainted Black	POF J	123K	ZIP	214K	Inches	4.92	4.92	2.10
						mm	125	125	53
1590WKF 1590WKFBK	Unpainted Black	>	115K	ZIP	120K	Inches	4.92	4.92	2.95
						mm	125	125	75
1590WJF 1590WJFBK	Unpainted Black	POF D	113K	ZIP	140K	Inches	5.71	3.74	1.77
				ZIP		mm	145	95	45
1590WP1F 1590WP1FBK	Unpainted Black	POE De	119K	ZIP	199K	Inches	6.01	3.24	1.81
						mm	153	82	46
1590WDDF 1590WDDFBK	Unpainted Black		130K	ZIP	314K	Inches	7.40	4.70	1.30
						mm	188	119.5	33
1590WDF 1590WDFBK	Unpainted Black	POF -	130K	ZIP	347K	Inches	7.38	4.70	2.05
						mm	188	120	52
1590WEF 1590WEFBK	Unpainted Black	POF	126K	ZIP	213K	Inches	7.38	4.70	3.07
						mm	188	120	78
1590WFF 1590WFFBK	Unpainted Black	POF	130K	ZIP	378K	Inches	7.38	7.38	2.48
						mm	188	188	63
1590WR1F 1590WR1FBK	Unpainted Black	POF }	128K	ZIP	229K	Inches	7.55	4.38	2.24
						mm	192	111	57

Link here to photo tables of each part number - note: regular, unflanged version shown for sizing

NOTES:

- For more detailed drawing of the enclosure refer back to our 1590 series (without flanges) listed above. This allowed more room on the drawings for other details.
- Dimensions are for enclosure (length does not include flanges)

- Add 0.16" (4 mm) to enclosure depth for lid
- For other drawing information or if you prefer .dwg versions of these drawings e-mail drawings@hammondmfg.com
- Available in natural vibra finish OR in light textured, powder paint in Black.
- This series is the same as our 1590 diecast aluminum except with a bead of rubberlike silicone around the perimeter of the lid.

DOWNLOAD

catalog pages on this series (132K) 9C-1590WF.pdf


Exactly what you are looking for??? Link to our stocking distributors - most have "on-line" pricing, stock check and ordering!!!



Home | Products | Distributors | Technical | Contact Us | Other Options

Copyright; © 1997-2005 Hammond Mfg Co Inc

URL: http://www.hammondmfg.com



www.hammondmfg.com