

CHEMTRONICS® Technical Data Sheet

TDS # CW8000

CircuitWorks® Flux Dispensing Pens

PRODUCT DESCRIPTION

CircuitWorks® Flux Dispensing Pens are designed specifically to apply each type of flux with precision control. The Rosin Flux Dispensing Pen quickly applies a noncorrosive type R flux. This flux meets MIL-F-14256 E and F. The No Clean Flux Dispensing Pen precisely applies a patented noncorrosive, halide free, organic low solid no clean flux. This flux meets Bellcore TR-NWT-000078 and IPC SF-818 for surface insulation resistance.


- Marker pen dispenser provides controlled and exact application
- Minimize excess flux waste
- Completely portable package
- All fluxes are noncorrosive and halide free
- Excellent material compatibility
- Fast drying

TYPICAL APPLICATIONS

CircuitWorks® Flux Dispensing Pens precisely dispense flux on:

- Printed Circuit Boards
- Chip Carriers
- Heat Sinks
- Surface Mount Device Pads
- Switches
- Sockets

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Rosin Flux Dispensing Pen	
Flux Type	Rosin, Grade WW
Flash Point (TCC)	54 °F (12 °C)
Vapor Density (air=1)	> 1
Appearance	Yellow Liquid
Odor	Alcohol
No Clean Flux Dispensing Pen	
Flux Type	Rosin, Grade WW
Flash Point (TCC)	54 °F (12 °C)
Vapor Density (air=1)	> 1
Appearance	Slightly Yellow Liquid
Odor	Alcohol
Shelflife	5 years
RoHS/WEEE Status	

COMPATIBILITY

CircuitWorks® Flux Dispensing Pens are generally compatible with most materials used in the electronics industry. As with any cleaning agent, material compatibility should be determined on a non-critical area prior to use.

USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

Hold pen vertically and briefly depress tip to start liquid flow. Rub pen tip on surface to be fluxed.

Wipe tip on a ControlWipe™ dry wipe to remove buildup.

CAUTION: Product is Flammable - Do not use near sources of ignition and energized equipment.

AVAILABILITY

CW8100 9 gm (0.32 oz) No Clean Flux Pen

CW8200 9 gm (0.32 oz) Rosin Flux Pen

NOTE: This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Information: 800-TECH-401

Product Identification

CIRCUITWORKS® NO CLEAN FLUX DISPENSING PEN

Product Code: CW8100, CW8100BLK

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Product Ingredient Information	CAS#	Wt. % Range
Isopropanol	67-63-0	10-90
Rosin	8050-09-7	5-20
Adipic acid	124-04-9	1-5
Dimethyl glutarate	1119-40-0	1-5

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Clear, yellow liquid with strong alcohol odor. This product is flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce drowsiness and a headache.

Potential Health Effects:

Eyes: Liquid and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation. Vapors released from the soldering process may cause eye irritation.

Skin: Prolonged contact may cause skin irritation and/or sensitization.

Ingestion: Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.

Inhalation: Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness and unconsciousness, with longer exposure. Vapors from soldering processes may cause irritation of the nose and throat. Respiratory sensitization may result from inhalation of rosin fumes.

Pre-Existing Medical Conditions Aggravated by Exposure: Heart, lung, skin, eye.

SECTION 4: FIRST AID MEASURES

Eyes: If eye irritation occurs immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persist. Wash clothing separately before reuse.

Ingestion: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but get immediate medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: 53°F (12C) (TCC)

LEL/UEL: Not established (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, OSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Not likely to occur.

Small Spills: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes and skin. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Avoid breathing product vapor or mist. Avoid breathing vapors given off by the soldering process. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Isopropanol	200 ppm	400 ppm	400 ppm
Rosin	NA	NA	NA

Work/Hygienic Practices: Ventilation is recommended to control airborne levels of soldering process vapors. Wear safety glasses with side shields (or goggles) and chemical resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	1	1
Flammability	3	3
Reactivity	1	1
Personal Protection	- B	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear, colorless liquid

Odor: Alcohol

pH: NA

Vapor Pressure: 37 mm Hg @ 68°F

Vapor Density: < 1

(Air = 1)

Boiling Point: 180°F (82C)

Solubility in Water: Soluble

Specific Gravity: (Water = 1) 0.830

Evaporation Rate: > 1

(Butyl acetate = 1)

Viscosity: 1 (Approx.)

(Water = 1)

Percent Volatile: < 99 %

SECTION 10: STABILITY AND REACTIVITY

Stability - This product is stable.

Conditions to Avoid: Do not use near open flames, red hot surfaces or other sources of ignition.

Incompatibility: Do not mix with strong acids or strong oxidizing agents.

Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION**Toxicological Information**

<u>Inhalation</u> :				<u>Ingestion</u> :		
Isopropanol	LC50/rats	12,000 ppm/8hr		Isopropanol	LD50 rats	5,045 mg/kg

<u>Skin</u> :				<u>Eye</u> :		
Isopropanol	Rabbit LD50	12,800 mg/kg		Isopropanol	rabbit	MLD-MOD

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none Teratogenic effects: none Mutagenic effects: none

SECTION 12: ECOLOGICAL INFORMATION**Environmental Impact Information**

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: **1-800-424-8802**

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATION

	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Class</u>	<u>Sub. Risk</u>	<u>Pkg. Group</u>	<u>Hazard Label</u>	<u>Pkg. Instr./Auth</u>	<u>Max. Quantity</u>
<u>Air</u> :	Flammable liquid n.o.s. (Isopropanol)	UN 1993	3	NA	II	Flammable liquid	305	1L
<u>Ground</u> :	Consumer Commodity ORM-D	NA	NA	--	NA	ORM-D	173.150	

SECTION 15: REGULATORY INFORMATION**SECTION 313 SUPPLIER NOTIFICATION**

This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class B2; Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

N Product should be used only with adequate ventilation. Mechanical ventilation is recommended on all soldering stations. If such ventilation is not available, personnel should wear NIOSH approved organic vapor respirators equipped with particulate dust filters specified for use during welding or soldering.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.