

Slim Line

Programmable keypad

ML technology with Gold Crosspoint contacts G84-4700



Typical applications

- Numerical input
- Control systems
- Frequent entry of numbers
- Extension for notebook computer

Key benefits

- Equally suitable for left- and righthanded users
- Low space requirements
- All keys can be user-defined with up to 24 characters per key
- 4 additional user-programmable function keys, can be labeled individually
- Digits can be entered independently of the status of the Num Lock in the system (operation on notebook PC)
- Variable decimal separator [.], [,], [00], or [000]
- External standard keyboard can be connected
- Matches design of Cherry keyboards G84-4100
- Uses mechanical keys from our ML series with high-precision key action; small physical dimensions:
- Reliability: MTBF: 550,000 hours

Technical specifications

Power supply: 3.3-5.0 V/DC ± 10% SELV

Current input: typ. 50 mA

Connecting cable: approx. 1.75 m long


Temperature range: Storage temperature: -20 °C to 60 °C Operating temperature: 0 °C to 50 °C

Dimensions of housing: $(L \times W \times H)$ 90 x 132 x 36 mm

Weight: approx. 260 g

ML key modules with Gold Crosspoint contacts

Actuation characteristics: Soft contact



Connection diagram

Stock codes

PS/2 male connector,

G84-4700 PRB..⁽¹⁾

PS/2 male connector,

PS/2 female connector for external keyboard black

G84-4700 PPB..⁽¹⁾

PS/2 female connector for external keyboard

(1) International layouts

		•
US	=	Belgian/Swiss
		English (US)/English (UK
DE	=	German
ES	=	Spanish
FR	=	French
IT	=	Italian
DK	=	Danish/Norwegian
SF	=	Swedish/Finnish

31

Other versions available on request.

c**¶**³us ₾ (€ FCC Part 15 Subpart B Class B Other approvals available on request.

30