



## Products

### LED Indicators

CML IT offers panel mount indicators manufactured with LED, Neon or Incandescent light sources. These indicators are available in a number of different lens and termination styles, with voltages of 2V ~ 250V available off-the-shelf.


### LED Indicator Search

Part Number  
Mounting Hole (inch)  
Mounting Hole (metric)  
Indicator Type  
Bezel Type  
Bezel Color  
Lens Type  
Indicator Color  
Op. Voltage (V)



[Download the full datasheet PDF](#)

[Back to LED Indicator Page](#)



**Part Number:** 19351133  
**Serial Number:** 1935  
**Mounting hole (inch):** 0.5512"  
**Mounting hole (metric):** 14mm  
**Indicator type:** standard  
**Mounting type:** with bezel  
**Bezel type:** prominent  
**Bezel material:** metal  
**Bezel color:** black chrome  
**Bezel size:** M14  
**Protection:** IP40  
**Lens type:** round  
**Lens color:** yellow diffused  
**Lens size:** 10mm  
**Connector tpe:** tab terminals 2.8x0.8  
**Connector number:** 2  
**Connector for lamp test:** no  
**Number LED chip:** 6  
**Indicator color:** yellow  
**Dom wave length:** 592nm  
**Peak wave length (mA):**  
**Op. voltage (V):** 130V AC  
**Forward volt max:**  
**Rectifier:** Half Wave  
**AC current:** 6mA  
**DC current:** -  
**Lum in min (mcd):**  
**Lum in type (DC):** 27mcd  
**Voltage type (%):** 10%  
**Op. temperature (°C):** -25 °C - +60 °C  
**Storage temperature (°C):** -25°C - +60°C  
**Narrative:** with protection tube  
**Viewing angle (°):**  
**RoHS Status:** Yes

