

PRODUCT SPECIFICATION

CATALOG NUMBER: See table below

CUSTOMER: Stock

DESCRIPTION: Outdoor use extension cord incorporating type SJTW cable

APPROVALS: UL Listed and CSA Certified Outdoor Use Cord Set

CONSTRUCTION PARAMETERS:

Conductor: See table below

Jacket material: PVC

Overall cable O.D. (nom): See table below


Cord rating: Hard Usage per the National Electric Code

Cable legend: Indent print

Attachment plug configuration: NEMA 5-15P
Cord connector configuration: NEMA 5-15R

Plug and connector material: PVC

16/3 - 12/3



10/3









ELECTRICAL PROPERTIES:

Cable temperature rating: -20 to +60 °C

Nominal operating voltage: 125 VAC

Maximum operating current: See table below

| Catalog number | Length | Conductor | Cable O.D. (nom) | Current rating |
|----------------|--------|----------------|------------------|----------------|
| 02304 | 10 ft | 16/3 26/30 BC | 0.315 in | 13A |
| 02305 | 15 ft | | | |
| 02306 | 15 ft | | | |
| 02307 | 25 ft | | | |
| 02308 | 50 ft | | | |
| 02309 | 100 ft | | | 10 A |
| 02407 | 25 ft | 14/3 41/30 BC | 0.352 in | 15A |
| 02408 | 50 ft | | | |
| 02409 | 100 ft | | | 13A |
| 02507 | 25 ft | 12/3 65/30 BC | 0.420 in | - 15A |
| 02508 | 50 ft | | | |
| 02509 | 100 ft | | | |
| 02607 | 25 ft | 10/3 104/30 BC | 0.567 in | |
| 02608 | 50 ft | | | |
| 02609 | 100 ft | | | |

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Systems. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Systems.