

## Cooper Bussmann

[Homepage](#)  
[About Cooper Bussmann](#)  
[Contact Us](#)  
[Privacy](#)  
[Legal](#)  
[Cooper Bussmann® Brand](#)  
[Site Map](#)

## AGX-30

Fast Acting, 1/4 X 1 Inch, Glass Tube Fuse

### Product Information

Product Type:	Fuse
Product Family:	Electronic
Brand:	Cooper Bussmann

### Recommended Products

Rec. Fuse Block:	<a href="#">3828-1</a>
Rec. Inline Fuse Holder:	<a href="#">HHB Series</a>
Rec. Fuse Clips:	<a href="#">1A1907 Series</a>

### Physical Properties

Dimensions:	1in.(L) × 0.25in.(W) × 0in.(H)
-------------	--------------------------------

### Electrical Properties

Maximum AC Voltage:	32
Amperage Rating:	30
AC Interrupting Ratings:	<ul style="list-style-type: none"><li>• 1000 at 32V</li></ul>
Fast Acting:	Yes
Resistance:	0.0022

# 1/4" x 1" Fuses

## AGX Series, Fast-Acting, Glass Tube

### Description

- Fast-acting glass tube fuse
- 1/4" x 1" (6.3 x 25.4mm) physical size
- Glass tube, nickel-plated brass endcap construction
- For instruments, electronic and small appliance circuits
- UL Listed product meets standard 248-14
- Available with axial leads



Electrical Characteristics		
Rated Current	% of Amp Rating	Opening Time
1/6 - 30A	110%	4 hours minimum
	135%	60 minutes maximum
1/6 - 2A	200%	5 seconds maximum
2.5 - 30A	200%	2 minutes maximum


### Agency Information

- UL Listed Card: AGX 0-5A (Guide JDYX, File E19180)
- UL Recognized Card: AGX 6-20A (Guide JDYX2, File E19180)
- CSA Component Acceptance Card (Class No. 1422-01, File 53787)

### Ordering

- Specify packaging, product, and option code

Dimensions - mm (in)




### Specifications

Part Number -(amps)	Voltage Rating Vac	Interrupting Rating (amps)			Typical DC Cold Resistance (Ω)*
		250Vac	125Vac	32Vac	
AGX-1/200	250	35	10,000	-	285.00000
AGX-1/100	250	35	10,000	-	155.00000
AGX-1/32	250	35	10,000	-	35.00000
AGX-1/16	250	35	10,000	-	22.50000
AGX-1/10	250	35	10,000	-	10.25000
AGX-1/8	250	35	10,000	-	5.41000
AGX-3/16	250	35	10,000	-	3.11500
AGX-2/10	250	35	10,000	-	2.66000
AGX-1/4	250	35	10,000	-	2.79000
AGX-3/10	250	35	10,000	-	1.42500
AGX-3/8	250	35	10,000	-	0.93050
AGX-4/10	250	35	10,000	-	0.89900
AGX-1/2	250	35	10,000	-	0.47850
AGX-3/4	250	100	10,000	-	0.26000
AGX-1	250	100	10,000	-	0.16250
AGX-1-1/4	250	100	10,000	-	0.12750
AGX-1-1/2	250	100	10,000	-	0.09400
AGX-2	250	100	10,000	-	0.06825
AGX-2-1/2	125	-	10,000	-	0.04930
AGX-3	125	-	10,000	-	0.03825
AGX-4	125	-	10,000	-	0.02700
AGX-5	125	-	10,000	-	0.02050
AGX-6	125	-	1000	-	0.01475
AGX-7	125	-	1000	-	0.01275
AGX-8	32	-	-	1000	0.01100
AGX-10	32	-	-	1000	0.00867
AGX-15	32	-	-	1000	0.00510
AGX-20	32	-	-	1000	0.00358
AGX-25	32	-	-	1000	0.00275
AGX-30	32	-	-	1000	0.00215

\* DC Cold Resistance (Measured at <10% of rated current)

# Time-Current Curve



Packaging	
Packaging Code Prefix	Description
BK	100 fuses packed into a cardboard carton

Option Code	
Option Code Suffix	Description
V	Axial leads - copper tinned wire with nickel plated brass overcaps