





## Performance Ratchet Cable Cutters


**Both models feature:**

- Simple, one-hand operation.
- Two-speed ratchet mechanism adjusts for light/heavy cutting.
- Well-suited for tight work spaces.
- Specially designed blade improves cutting capacity.

CAT. NO.	UPC NO.	DESCRIPTION	WEIGHT	
			LBS.	kg
45206	45206	Performance Ratchet Cable Cutter	1.5	.7
45207	45207	Performance Ratchet Cable Cutter	2.4	1.1
45218	45218	 Movable Blade (45206)		
45212	45212	 Fixed Blade (45206)		
45211	45211	 Movable Blade (45207)		
45228	45228	 Fixed Blade (45207)		





**SPECIFICATIONS**

	Copper	Aluminum	Communications Cable
<b>45206</b>			
<b>Maximum Capacity*</b>	600 kcmil (MCM) (300 mm <sup>2</sup> )	600 kcmil (MCM) (300 mm <sup>2</sup> )	1-3/8" (35 mm) dia.
<b>Frequent Use Capacity*</b>	500 kcmil (MCM) (240 mm <sup>2</sup> )	500 kcmil (MCM) (240 mm <sup>2</sup> )	
<b>Length</b>	10" (254 mm)		
<b>Jaw opening</b>	1-7/16" (36.5 mm)		
<b>45207</b>			
<b>Maximum Capacity*</b>	750 kcmil (MCM) (400 mm <sup>2</sup> )	1000 kcmil (MCM) (500 mm <sup>2</sup> )	2" (51 mm) dia.
<b>Frequent Use Capacity*</b>	600 kcmil (MCM) (300 mm <sup>2</sup> )	750 kcmil (MCM) (400 mm <sup>2</sup> )	
<b>Length</b>	11" (279 mm)		
<b>Jaw opening</b>	2" (51 mm)		

## Compact Ratchet Cable Cutters



- Simple, one-hand operation.
- Compact – convenient for working in tight places and stores easily in tool pouches.
- Single-speed ratchet mechanism.
- Blade release allows blades to be opened in mid-cut.
- Heavy-duty blades provide long life.

CAT. NO.	UPC NO.	DESCRIPTION
759	45277	Compact Ratchet Cable Cutter
760	17600	Compact Ratchet Cable Cutter
45282	45282	 Movable Blade (759)
45281	45281	 Fixed Blade (759)
09908	09908	 Movable Blade (760)
09907	09907	 Fixed Blade (760)

**SPECIFICATIONS**

	Copper	Aluminum	Communications Cable
<b>759</b>			
<b>Maximum Capacity*</b>	500 kcmil (MCM) (240 mm <sup>2</sup> )	750 kcmil (MCM) (400 mm <sup>2</sup> )	1-1/8" dia. (28 mm <sup>2</sup> )
<b>Frequent Use Capacity*</b>	400 kcmil (MCM) (185 mm <sup>2</sup> )	600 kcmil (MCM) (300 mm <sup>2</sup> )	
<b>Length</b>	10-1/2" (262 mm)		
<b>Weight</b>	1.4 lbs. (0.6 kg)		
<b>760</b>			
<b>Maximum Capacity*</b>	1000 kcmil (MCM) (500 mm <sup>2</sup> )	1000 kcmil (MCM) (500 mm <sup>2</sup> )	1-3/4" dia. (42 mm <sup>2</sup> )
<b>Frequent Use Capacity*</b>	750 kcmil (MCM) (400 mm <sup>2</sup> )	1000 kcmil (MCM) (500 mm <sup>2</sup> )	
<b>Length</b>	11-3/4" (298 mm)		
<b>Weight</b>	1.75 lbs. (0.8 kg)		

\*Capacity may be less for compact and compressed cables