











**3/8" TIPS**

**3/8" (9.5mm) Plato® Tips to fit Soldering Irons For  
Hexacon® • American Beauty® • Esico®**









| Hexacon® | PLATO® | PLATO® TIP                                                                         | Tip drawings are actual size.                                                       |
|----------|--------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| HT449    | 66-300 |  |  |
| HT470    | 66-349 |  |  |
| HT472    | 66-911 |  |  |
| ---      | 66-627 |  |  |
| ---      | 66-704 |  |  |

All points are 1/16" (1.6) thick unless otherwise noted. ( ) = mm

Tip samples are available. Custom tip designs on request. All dimensions are shown before tinning and are subject to manufacturing tolerances.

**5/8" TIPS**

**5/8" (15.9mm) Plato® Tips to fit Soldering Irons For  
• Hexacon® • American Beauty® • Esico® • Weller® Marksman SP175**

| Hexacon® | PLATO®   | PLATO® TIP                                                                           | Tip drawings are actual size.                                                         |
|----------|----------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| HT178    | 1010-397 |  |  |
| HT256    | 1010-286 |  |  |
| HT891    | 1010-104 |  |  |
| HT499    | 1010-184 |  |  |

All points are 1/16" (1.6) thick unless otherwise noted. ( ) = mm

Tip samples are available. Custom tip designs on request. All dimensions are shown before tinning and are subject to manufacturing tolerances.