



Voltage control

Designation

Part number

Description

Operating conditions

conditions

Control values

Supply voltage

Time delay

Output relay

MUS12DC	84872140	Undervoltage or Overvoltage	-	9-15 V DC	Self-powered 12 V DC	0,1 s to 10 s	1 single changeover relay 5 A
MUS80ACDC	84872141	Undervoltage or Overvoltage	-	20-80 V AC/DC	Self-powered 24-48 V AC/DC	0,1 s to 10 s	1 single changeover relay 5 A
MUS260ACDC	84872142	Undervoltage or Overvoltage	-	65-260 V AC/DC	Self-powered 110-240 V AC/DC	0,1 s to 10 s	1 single changeover relay 5 A
MUSF80ACDC	84872151	Undervoltage or Overvoltage (window)	-	20-80 V AC/DC	Self-powered 24-48 V AC/DC	0,1 s to 10 s	1 single changeover relay 5 A
MUSF260ACDC	84872152	Undervoltage or Overvoltage (window)	-	65-260 V AC/DC	Self-powered 110-240 V AC/DC	0,1 s to 10 s	1 single changeover relay 5 A
HUL	84872120	Undervoltage or Overvoltage	-	0,2 V to 2 V 1 V to 10 V 6 V to 60 V	24-240 V AC/DC 50/60 Hz	0,1 s to 3 s	1 double changeover relay 2 X 5A
HUH	84872130	Undervoltage or Overvoltage	-	15 V to 150 V 30 V to 300 V 60 V to 600 V	24-240 V AC/DC 50/60 Hz	0,1 s to 3 s	1 double changeover relay 2 X 5A