


88974033 : Millenium 3 Custom - Custom "Compact" range without display - CB20 Custom

- ✓ "Modular" versions designed for Custom application-specific functions (Custom functions)
- ✓ No display or parameter-setting buttons to avoid tampering by unauthorised users



| Part number characteristics | 88974033 |
|-----------------------------|---------------|
| Input | 12 digital |
| Output | 8 relays 8 A |
| Supply | 100 →240 V AC |

General characteristics

| 88974033 : Millenium 3 Custom - Custom "Compact" range without display - CB20 Custom | |
|--|---|
| General characteristics | |
| | See page 22, except: |
| Certifications | UL, CSA |
| Operating temperature | -30 →+70°C (DC) ; -20 →+70° C (AC) ; Operating temperature @ 100% (Relays 6A) Operating temperature @ 66% (Relays 8A) |
| Storage temperature | -40 →+80°C |
| General environment characteristics for CB, CD, XD, XB, XR and XE product types | |
| Certifications | UL, CSA GL: except for 88 970 32x (pending) |
| Conformity with the low voltage directive | In accordance with 73/23/EEC: EN (IEC) 61131-2 (Open equipment) |
| Conformity with the EMC directive | In accordance with 89/336/EEC: EN (IEC) 61131-2 (Zone B) EN (IEC) 61000-6-2, EN (IEC) 61000-6-3 (*) EN (IEC) 61000-6-4 (*) Except configuration (88 970 1.1 or 88 970 1.2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B: pending) |
| Earthing | None |
| Protection rating | In accordance with IEC/EN 60529: IP40 on front panel IP20 on terminal block |
| Overvoltage category | 3 in accordance with IEC/EN 60664-1 |
| Pollution | Degree: 2 in accordance with IEC/EN 61131-2 |
| Maximum utilisation altitude | Operation: 2000 m Transport: 3048 m |
| Mechanical resistance | Immunity to vibrations IEC/EN 60068-2-6, Fc test Immunity to shock IEC/EN 60068-2-2, Fa test |
| Resistance to electrostatic discharge | Immunity to ESD IEC/EN 61000-4-2, level 3 |
| Resistance to HF interference | Immunity to radiated electrostatic fields IEC/EN 61000-4-3 Immunity to fast transients (burst immunity) IEC/EN 61000-4-4, level 3 Immunity to shock waves IEC/EN 61000-4-5 Radio frequency in common mode IEC/EN 61000-4-6, level 3 Voltage dips and breaks (AC) IEC/EN 61000-4-11 |

| | |
|-------------------------------------|---|
| | Immunity to damped oscillatory waves IEC/EN 61000-4-12 |
| Conducted and radiated emissions | Class B (*) in accordance with EN 55022/11 group 1 (* Except configuration (88 970 1.1 or 88 970 1.2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B: pending) |
| Operating temperature | -20 → +55°C (+40°C in a non-ventilated enclosure) in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2 |
| Storage temperature | -40 → +70°C in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2 |
| Relative humidity | 95% max. (no condensation or dripping water) in accordance with IEC/EN 60068-2-30 |
| Screw terminals connection capacity | Flexible wire with ferrule = 1 conductor: 0.25 to 2.5 mm (AWG 24...AWG 14) 2 conductors 0.25 to 0.75 mm (AWG 24...AWG 18) Semi-rigid wire = 1 conductor: 0.2 to 2.5 mm (AWG 25...AWG 14) Rigid wire = 1 conductor: 0.2 to 2.5 mm (AWG 25...AWG 14) 2 conductors 0.2 to 1.5 mm (AWG 25...AWG 16) Tightening torque = 0.5 N.m (4.5 lb-in) (tighten using screwdriver diam. 3.5 mm) |

