



## Series GFT/GB

### Features

- ✓ **Superior Construction** - All terminals are molded in place with precision screw machined brass inserts which will not twist, virtually eliminating broken solder joints while providing a full mechanical thread system.
- ✓ **Ideal for Sub-Chassis or Thru-panel Application** - No costly insulation or mounting set-up since feed-thru insulators are an integral part of the moldings. Feature provides a full 1/4" terminal to ground clearance even thru 1/16" chassis.
- ✓ **Durable Base Material** - Made of black thermo-set phenolic, or high-impact, break resistant thermoplastic.
- ✓ **Electrical Rating** - 20 amps/up to 600 volts
- ✓ **Compact Barrier-Type Design** - Especially suited for electronic and control applications.
- ✓ **Feed-Thru, Printed Circuit or Surface Connection** - One thru 26 terminals on 7/16" center-to-center spacing.
- ✓ **Broad Wire Range** - UL Recognized for No. 22AWG to No. 12AWG, depending on type of external contact designated, with CSA requiring use of lugs on wire larger than 16AWG.
- ✓ **Terminal Flexibility** - External terminals available in three screw sizes with various internal terminal types.
- ✓ **Metric Screws** - Available in GBPX and GFTX Series for export applications



 Recognized under the Components Program of Underwriters Laboratories, Inc. Standard 1059, Guide No. XCFR2, File No.E62557.

 Guide No.184-N-90, Report No.LR39186-1.

### Variations