

Filter Inductors High Current



ELECTRICAL SPECIFICATIONS

Inductance: Measured at 1.0 V with no DC current

Incremental Current: The typical current at which the inductance will be decreased by 5 % from its initial zero DC value

Dielectric Rating: 2500 VRMS between winding and outer circumference to within 0.250" [6.35 mm] of the insulating sleeve edge

Operating Temperature: - 55 °C to + 125 °C (no load)
- 55 °C to + 85 °C (at full rated current)

Current Rating: Maximum continuous Operating current (DC or RMS) based on a 40 °C temperature rise

FEATURES

- Printed circuit mounting (axial leads)
- Protected by polyolefin tubing
- High saturation bobbin used allowing high inductance with low DC resistance
- Pre-tinned leads
- High resistivity core offers very high parallel resistance, resulting in maximum coil performance
- 20 sleeveless models available at reduced cost


RoHS
COMPLIANT

MECHANICAL SPECIFICATIONS

Wire: Solid soft copper

Terminals: 20 AWG tinned copper leads

Coating: Polyolefin tubing - flame retardant UL type VW-1 per MIL-I-23053/5, Class 3 requirements

Core Material: Ferrite

DIMENSIONS in inches [millimeters]		
MODEL	A (Max.)	B (Max.)
IHD-1	0.270 [6.85]	0.700 [17.78]
IHD-3	0.460 [11.68]	0.900 [22.86]

STANDARD ELECTRICAL SPECIFICATIONS									
IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)	IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)
MODEL IHD-1									
1.0	± 15 %	0.009	5.3	7.00	56.0	± 15 %	0.130	1.4	0.97
1.2	± 15 %	0.010	5.0	6.40	68.0	± 15 %	0.145	1.3	0.88
1.5	± 15 %	0.011	4.8	5.70	82.0	± 15 %	0.152	1.3	0.80
1.8	± 15 %	0.012	4.6	5.20	100.0	± 15 %	0.208	1.1	0.73
2.2	± 15 %	0.013	4.4	4.70	120.0	± 15 %	0.283	0.94	0.66
2.7	± 15 %	0.014	4.2	4.30	150.0	± 15 %	0.330	0.87	0.60
3.3	± 15 %	0.016	4.0	3.90	180.0	± 15 %	0.362	0.83	0.54
3.9	± 15 %	0.017	3.8	3.60	220.0	± 15 %	0.505	0.70	0.49
4.7	± 15 %	0.022	3.4	3.30	270.0	± 15 %	0.557	0.67	0.45
5.6	± 15 %	0.024	3.2	3.00	330.0	± 15 %	0.650	0.62	0.40
6.8	± 15 %	0.026	3.1	2.70	390.0	± 15 %	0.770	0.57	0.37
8.2	± 15 %	0.028	3.0	2.50	470.0	± 15 %	1.030	0.49	0.34
10.0	± 15 %	0.033	2.8	2.30	560.0	± 15 %	1.140	0.47	0.31
12.0	± 15 %	0.037	2.6	2.10	680.0	± 15 %	1.500	0.41	0.28
15.0	± 15 %	0.040	2.5	1.90	820.0	± 15 %	1.980	0.36	0.26
18.0	± 15 %	0.044	2.4	1.70	1000.0	± 15 %	2.300	0.33	0.23
22.0	± 15 %	0.050	2.2	1.50	1200.0	± 15 %	2.550	0.31	0.21
27.0	± 15 %	0.070	1.9	1.40	1500.0	± 15 %	3.000	0.29	0.19
33.0	± 15 %	0.075	1.8	1.30	1800.0	± 15 %	4.000	0.25	0.18
39.0	± 15 %	0.084	1.7	1.20	2200.0	± 15 %	4.400	0.24	0.16
47.0	± 15 %	0.104	1.6	1.10	2700.0	± 15 %	5.800	0.21	0.14



STANDARD ELECTRICAL SPECIFICATIONS									
IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)	IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)
MODEL IHD-1									
3300.0	± 15 %	6.560	0.20	0.13	8200.0	± 15 %	20.800	0.11	0.08
3900.0	± 15 %	8.630	0.17	0.12	10000.0	± 15 %	23.400	0.10	0.08
4700.0	± 15 %	10.100	0.16	0.11	12000.0	± 15 %	26.000	0.10	0.07
5600.0	± 15 %	11.200	0.15	0.10	15000.0	± 15 %	36.000	0.08	0.06
6800.0	± 15 %	15.000	0.13	0.09	18000.0	v	40.000	0.08	0.06
MODEL IHD-3									
3.9	± 15 %	0.007	4.0	8.20	680.0	± 15 %	0.570	1.0	0.67
4.7	± 15 %	0.008	4.0	7.50	820.0	± 15 %	0.643	0.8	0.61
5.6	± 15 %	0.011	4.0	6.90	1000.0	± 15 %	0.844	0.8	0.56
6.8	± 15 %	0.011	4.0	6.30	1200.0	± 15 %	0.977	0.6	0.51
8.2	± 15 %	0.013	4.0	5.70	1500.0	± 15 %	1.180	0.6	0.46
10.0	± 15 %	0.016	4.0	5.20	1800.0	± 15 %	1.500	0.6	0.42
12.0	± 15 %	0.018	4.0	4.70	2200.0	± 15 %	1.760	0.5	0.38
15.0	± 15 %	0.020	4.0	4.30	2700.0	± 15 %	2.130	0.4	0.34
18.0	± 15 %	0.022	4.0	3.90	3300.0	± 15 %	2.530	0.4	0.31
22.0	± 15 %	0.024	4.0	3.50	3900.0	± 15 %	2.840	0.4	0.29
27.0	± 15 %	0.025	4.0	3.20	4700.0	± 15 %	3.790	0.4	0.26
33.0	± 15 %	0.028	4.0	2.90	5600.0	± 15 %	4.240	0.32	0.24
39.0	± 15 %	0.031	4.0	2.70	6800.0	± 15 %	5.750	0.25	0.22
47.0	± 15 %	0.034	4.0	2.50	8200.0	± 15 %	6.440	0.25	0.20
56.0	± 15 %	0.043	3.2	2.30	10000.0	± 15 %	7.300	0.25	0.18
68.0	± 15 %	0.059	2.5	2.10	12000.0	± 15 %	9.340	0.20	0.17
82.0	± 15 %	0.066	2.0	1.90	15000.0	± 15 %	10.700	0.20	0.15
100.0	± 15 %	0.084	1.6	1.70	18000.0	± 15 %	14.800	0.16	0.14
120.0	± 15 %	0.113	1.6	1.60	22000.0	± 15 %	18.000	0.13	0.12
150.0	± 15 %	0.129	1.6	1.40	27000.0	± 15 %	22.700	0.13	0.11
180.0	± 15 %	0.150	1.6	1.30	33000.0	± 15 %	25.700	0.13	0.10
220.0	± 15 %	0.162	1.6	1.20	39000.0	± 15 %	29.700	0.10	0.09
270.0	± 15 %	0.226	1.6	1.10	47000.0	± 15 %	33.700	0.10	0.09
330.0	± 15 %	0.257	1.6	0.95	56000.0	± 15 %	38.000	0.10	0.08
390.0	± 15 %	0.288	1.6	0.88	68000.0	± 15 %	52.800	0.08	0.07
470.0	± 15 %	0.393	1.2	0.80	82000.0	± 15 %	67.300	0.07	0.07
560.0	± 15 %	0.504	1.0	0.74	100000.0	± 15 %	76.000	0.07	0.06

MARKING
- Vishay Dale
- Model
- Value
- Date code

ORDERING INFORMATION				
IHD-1	3.9 μH	± 15 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION			
I H D 1	E R	3 R 9	L
MODEL	PACKING CODE	INDUCTANCE VALUE	TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.