

Providing Engineered Solutions for Your Plastic Component Needs

Products

- Knobs
- Handles
- Instrument Cases & Covers
- Handwheels
- Two Shot / Soft Touch

Decorative Husky & Trigon Knobs

The Husky and Trigon are both very durable knobs, with knurled edges to provide the best grip possible. Add that special touch to these plastic knobs by adding an inlay with your company logo or special instructions.

- Varieties available in both thermoplastic and phenolic materials.
- Sizes ranging from 3/4" to 2-1/2" in diameter.
- Female insert, projecting stud and thru-hole options are available. Please see the chart below for a complete list of our capabilities for each part number.
- Knobs can be decorated or customized to your specific need.
- Can't find what you're looking for? <u>Contact us</u> today to learn about our <u>custom molding</u> <u>options</u>.

Husky Knobs







2850/2855/2860

2870/2890

2851


						Threaded Female Insert											Threaded Male Stud*											Threaded Femal Insert Thru-Hole										
		А	В		С	Γ	Γ	Τ	Ţ		8	zi.				Ţ				_	ω;	ŧ				П	T	T,	J	٥	6-24				_			
Material Type	Part No.	Dia.	Current Part Height	Part Height Capab.	Hub Dia.	8-32	10.04	1000	200	1/4-28	5/16-1	5/16-2	3/8-16	3/8-24	1200	8.30	10-24	10-32	1/4-20	1/4-28	5/16-1	3/01/0	3/8-24	1-2/13	1/2-20	8-32	10-24	10-32	S 3	€]₹	5/16-2	183	1189	1654	1/2-20			
TS	2850	1	7/8	.875-1.000	3/4		Δ	ı.		A		Δ		A	A. A	A A	Δ	Δ									Α		4	N.	A		Δ	A	Δ.			
TS	2855	3/4	35/64, 5/8, 11/16	.547750	1/2	•		۱	۱	•	A	٨									۱							۱	4	4	4							
TS	2860	1 3/16	13/16	N/A	13/16	▲	Δ	A A	N.	A		Δ		A /	A A	A	A	Δ				T	F			Δ	4	A.	4	N.	A		Δ	Δ.	Δ.			
TS	2870	1 5/8	7/8	N/A	1 5/32	Δ	Δ	l d	N.	A				A /	A A	A A	Α	Δ						Δ	Δ	Δ	Δ,	A.	4	N.			Δ	Δ.	Δ.			
TS	2890	2 1/2	1 1/2	N/A	1 1/4	▲	Δ	L A	N.	A		Δ			4	A A	A	Δ								▲	Δ.	A.	4	N.	A				Δ.			
TP	2851	1	7/8	.875-1.000	3/4	A	Δ	k d	A A	A		Α	Δ.	Δ.	h, d	A A						A	A	A	Δ	▲	Δ	A.	A A	N A	A	Δ		▲.	Δ.			

For parts with male studs. LENGTH projecting below knob must be specified.

Trigon Knobs

 [■] Currently Manufacture/Tooled
 ▲ Could Manufacture/Requires Tooling

TS Thermoset TP Thermoplastic



						Threaded Female Insert															de										i Fe					
		А	В		C		Γ	Г			8	st.					П	T			0 5	ŧ				Г	П				20 7	* .	I	T		_
Material Type	Part No.	Dia.	Current Part Height	Part Height Capab.	Hub Dia.	8-32	10-24	10-32	1/4-20	1/4-28	5/16-1	5/16-2	3/8-16	1-2/13	1/2-20	8-32	10-24	10-32	1/4-20	97-6/1	0/10-	3/8-16	3/8-24	1-2/13	1/2-20	8-32	10-24	10-32	1/4-20	1/4-28	5/16-1	3/01/0	2/0-10	1-0/13	1/2.20	1
TP	3070	3/4	33/64, 5/8, 23/32	.813-1.000	15/32														•																	_
TP	3071	1	13/16	.625-1.000	5/8					Δ				l.								A								Δ.			ı	A.		
TP	3076	2 1/4	1 7/64	N/A	23/32	▲	Δ	Δ		Δ		Δ		A		Δ	Δ	Α		1	A A	ı.		Α	Δ	Δ	Δ	<u>.</u>		Δ	1	A.	A	A	A	_
TS	3072	1 1/4	5/8, 7/8	.625-1.000	3/4	▲	Δ	Δ		Δ.				A		▲	▲	A						A	Δ	Δ	Δ.	A		Δ.			ı	A		
TS	3073	1 5/8	13/16, 7/8	.750-1.000	3/4	▲				Δ		Δ.		A	A	A	Δ	Δ						Α	Δ	Δ				Δ	1	h.	A	A	A	_
TS	3075	2 1/8	7/8, 1 13/64, 1 1/4	N/A	1	A	A	A		A		A				A	▲	A								A	A	A		A	•	h.				Ī

^{*} For parts with male studs. LENGTH projecting below knob must be specified.

Currently Manufacture/Tooled

Could Manufacture/Requires Tooling
TS Thermoset
TP Thermoplastic

Davies Molding, L.L.C. | 350 Kehoe Blvd. | Carol Stream, IL 60188-1818 | Phone: 800-554-9208 | Fax: 630-510-9944