


Computer Cable

MULTICONDUCTOR OVERALL ALUMYLAR™ SHIELDED CABLE

Standard Putups: <ul style="list-style-type: none"> • 100 ft. • 500 ft. • 1000 ft. • bulk. 	DESCRIPTION <ul style="list-style-type: none"> • Construction: Conductors cabled with overall shield. • Conductors: Stranded tinned copper. • Insulation: Color coded polyvinylchloride. • Shield: Alumylar(TM) overall shield (100% coverage) with stranded tinned copper drain wire. • Jacket: Chrome polyvinylchloride. 	FEATURES & APPLICATIONS <ul style="list-style-type: none"> • Alumylar(TM) shield with drain wire offers ease of termination and high reliability. For sound, broadcast, instrumentation and computer cables for EIA RS-232 applications.
	CHARACTERISTICS <ul style="list-style-type: none"> • Voltage Rating: 300 Volts AWM. 	APPROVALS <ul style="list-style-type: none"> • UL: 2464 • CSA: AWM II A/B FT4 • Recognized under the components program of Underwriters' Laboratories, Inc. UL Style 2464. CSA AWM II A/B FT4. NEC Type CL2. Passes VW-1 Vertical Flame Test. OSHA Acceptable.

	Part Number	No. of Conductors	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. Jacket Thickness in. mm	Nom. O.D. in. mm	Color Code
	1012210	10	22	7/30	.030 0.76	.010 0.25	.032 0.81	.269 6.83	1