

Coaxial Cable

Computer Cable
MULTIPAIR OVERALL ALUMYLAR™ SHIELDED CABLE

<p>Standard Putups:</p> <ul style="list-style-type: none"> • 100 ft. • 500 ft. • 1000 ft. • bulk. <p>See color charts 4, 9 or 10 (as noted) in Technical Section.</p>	<p>DESCRIPTION</p> <ul style="list-style-type: none"> • Construction: Paired conductors with overall shield. • Conductors: Stranded tinned copper. • Insulation: Color coded polyvinylchloride. • Shield: Alumylar(TM)overall with stranded tinned copper drain wire. • Jacket: Chrome polyvinylchloride. <p>CHARACTERISTICS</p> <ul style="list-style-type: none"> • Temperature: 80C AWM - 90C CL2. • Voltage Rating: 300 Volts AWM. • Resistant To: Acids, alkalis, oil, moisture, solvents and fungus. 	<p>FEATURES & APPLICATIONS</p> <ul style="list-style-type: none"> • Alumylar(TM) shield with drain wire offers ease of termination and reliability. *Designed for use in instrumentation and computer applications. <p>APPROVALS</p> <ul style="list-style-type: none"> • UL: 2464 • CSA: AWM II A/B FT4 • Recognized under the components program of Underwriters' Laboratories, Inc. UL Style 2464. CSA AWM II A/B FT4. NEC Type CL2. Passes VW-1 Vertical Flame Test. OSHA Acceptable.
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Part Number	No. of Pairs	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. Jacket Thickness in. mm	Nom. O.D. in. mm	Color Code
1022401	1	24	7/32	.024 0.61	.010 0.25	.032 0.81	.156 3.81	4
1022402	2	24	7/32	.024 0.61	.010 0.25	.032 0.81	.222 5.64	4
1022403	3	24	7/32	.024 0.61	.010 0.25	.032 0.81	.232 5.89	4
1022404	4	24	7/32	.024 0.61	.010 0.25	.032 0.81	.265 6.73	4
1022405	5	24	7/32	.024 0.61	.010 0.25	.035 0.89	.295 7.49	4
Part Number	No. of Pairs	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. Jacket Thickness in. mm	Nom. O.D. in. mm	Color Code
1022406	6	24	7/32	.024 0.61	.010 0.25	.035 0.89	.295 7.49	4
1022407	7	24	7/32	.024 0.61	.010 0.25	.035 0.89	.300 7.62	4
1022408	8	24	7/32	.024 0.61	.010 0.25	.035 0.89	.330 8.38	4
1022409	9	24	7/32	.024 0.61	.010 0.25	.035 0.89	.340 8.64	4
1022410	10	24	7/32	.024 0.61	.010 0.25	.040 1.02	.380 9.65	4
Part Number	No. of Pairs	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. Jacket Thickness in. mm	Nom. O.D. in. mm	Color Code
1022415	15	24	7/32	.024 0.61	.010 0.25	.040 1.02	.425 10.80	4
1022419	19	24	7/32	.024 0.61	.010 0.25	.040 1.02	.450 11.43	4
1022425	25	24	7/32	.024 0.61	.010 0.25	.045 1.14	.515 13.08	4
1022450	50	24	7/32	.024 0.61	.010 0.25	.050 1.27	.700 17.78	CF
1022202	2	22	7/30	.030 0.76	.010 0.25	.032 0.81	.230 5.84	10
Part Number	No. of Pairs	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. Jacket Thickness in. mm	Nom. O.D. in. mm	Color Code
1022203	3	22	7/30	.030 0.76	.010 0.25	.032 0.81	.250 6.35	10
1022204	4	22	7/30	.030 0.76	.010 0.25	.032 0.81	.270 6.86	10