




Company Profile
and History



Product
Quote Form



Find a
Distributor



Contact Us

Product Index



Hookup Wire

Braided Stranded Copper Wire

Multiconductor

Tubing

Coaxial Cable

Check the Items You'd Like to Add to Your Quote or Order

Military Specification Hookup Wire

POLYTETRAFLUOROETHYLENE (PTFE) INSULATION

*MIL-W-16878/4 (PREVIOUSLY TYPE 'E')

Standard

Putups:

- 100 ft.
- 1000 ft.

See color chart
8 in Technical
Section. Consult
factory for
availability of
other colors and
color
combinations.

DESCRIPTION

- Conductors: Silver-plated copper with 40 microinches minimum coating thickness per ASTM B-298. Also available on special order are constructions with nickel-plated copper, silver-plated or nickel-plated, high-strength high-conductivity copper alloy.
- Insulation: Extruded PTFE, nominal wall .010 (0.25mm). Bondable treated or sodium-etched coating can be supplied upon request.
- Color Coding: Insulation color coding to MIL-STD-104 is available in solid colors and stripes.

CHARACTERISTICS

- Temperature Range: -55C to +200C with silver-plated conductors. -55C to +260C with nickel-plated conductors.
- Insul. Flaw Test (Spark Test): 4,600 Volts rms @ 3.0 kHz.
- Min. Insul. Resist.: Meets specification requirements.
- Heat Resistance: +290C for 96 hours.
- Voltage Rating: 600 Volts rms.

FEATURES & APPLICATIONS

- This wire insulated with PTFE is rated at 600 volts rms, with the corresponding DC potential at 1,500 volts. Suitable for high-frequency use at elevated temperatures in high-reliability programs where electrical and thermal stability are important.

APPROVALS

- Passes VW-1 Vertical Flame Test. OHSAA Acceptable. MIL-W-16878/4 (previously Type 'E').

Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
13201	32	Solid	.008 0.20	.028 0.71	M16878/4BAA
13207	32	7/40	.009 0.23	.029 0.74	M16878/4BAB
13219	32	19/44	.010 0.25	.030 0.76	N/A
13001	30	Solid	.010 0.25	.030 0.76	M16878/4BBA
13007	30	7/38	.012 0.30	.032 0.81	M16878/4BBB
Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
13019	30	19/42	.012 0.30	.030 0.76	N/A
12801	28	Solid	.013 0.33	.033 0.64	M16878/4BCA
12807	28	7/36	.015 0.38	.035 0.89	M16878/4BCB*
12819	28	19/40	.015 0.38	.035 0.89	N/A
12601	26	Solid	.016 0.41	.036 0.91	M16878/4BDA
Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
12607	26	7/34	.019 0.48	.039 0.99	M16878/4BDB
12619	26	19/38	.019 0.48	.039 0.99	M16878/4BDE*
12401	24	Solid	.020 0.51	.040 1.02	M16878/4BEA
12407	24	7/32	.024 0.61	.044 1.12	M16878/4BEB
12419	24	19/36	.024 0.61	.044 1.12	M16878/4BEE*
Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
12201	22	Solid	.025 0.64	.045 1.14	M16878/4BFA
12207	22	7/30	.030 0.76	.050 1.27	M16878/4BFB
12219	22	19/34	.030 0.76	.050 1.27	M16878/4BFE*
12001	20	Solid	.032 0.81	.052 1.32	M16878/4BGA
12007	20	7/28	.038 0.97	.058 1.47	M16878/4BGB
Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
12019	20	19/32	.038 0.97	.058 1.47	M16878/4BGE*
11801	18	Solid	.040 1.02	.060 1.52	M16878/4BHA
11807	18	7/26	.048 1.22	.068 1.73	M16878/4BHB
11819	18	19/30	.047 1.19	.068 1.73	M16878/4BHE*

	11619	16	19/29	.053 1.35	.076 1.98	M16878/4BJE*
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. O.D. in. mm	Military Number
	11419	14	19/27	.067 1.70	.093 2.36	M16878/4BKE*
	11219	12	19/25	.084 2.13	.111 2.62	M16878/4BLE*
	11037	10	37/26	.110 2.79	.138 3.51	M16878/4BMG*

CF-Consult factory. N/A-Not available as M16878. *Also available in latest revision of MIL-W-22759/11. Manufactured to latest available revision without surface marking. Other AWG's and strandings available upon request (see NEMA HP-3).

If you wish to add the products to your quote or complete your quote check one of these buttons

[Home](#) | [Profile](#) | [Catalog](#) | [Quote Form](#) | [Representatives](#) | [Contact](#)

Copyright 1997-2001, Dearborn Wire and Cable, Inc.