



Lacing Tape and Twine
MILITARY GRADE NYLON LACING TAPE
 *MIL-T-43435B, TYPE I

DESCRIPTION

• Construction: Flat braid manufactured from high tenacity, continuous filament nylon yarn.

CHARACTERISTICS

• Temperature Range: -55 to +121C.

FEATURES & APPLICATIONS

• For use in bundling military wire harnesses. *Nylon has excellent tensile strength and resists acids, abrasion, flame and fungus.

APPROVALS

• MIL-T-43435B, Type I.

Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
813530W	1	135 lbs.	.200 5.08	.016 0.41	Natural	A	250 yds.
813530B	1	135 lbs.	.200 5.08	.016 0.41	Black	A	250 yds.
813536W	1	135 lbs.	.200 5.08	.016 0.41	Natural	B	250 yds.
813536B	1	135 lbs.	.200 5.08	.016 0.41	Black	B	250 yds.
813540W	1	135 lbs.	.200 5.08	.016 0.41	Natural	C	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
813540B	1	135 lbs.	.200 5.08	.016 0.41	Black	C	250 yds.
813532W	1	135 lbs.	.200 5.08	.016 0.41	Natural	E	250 yds.
813532B	1	135 lbs.	.200 5.08	.016 0.41	Black	E	250 yds.
808030W	2	80 lbs.	.110 2.79	.015 0.38	Natural	A	250 yds.
808030B	2	80 lbs.	.110 2.79	.015 0.38	Black	A	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
808036W	2	80 lbs.	.110 2.79	.015 0.38	Natural	B	250 yds.
808036B	2	80 lbs.	.110 2.79	.015 0.38	Black	B	250 yds.
808040W	2	80 lbs.	.110 2.79	.015 0.38	Natural	C	250 yds.
808040B	2	80 lbs.	.110 2.79	.015 0.38	Black	C	250 yds.

808032W	2	80 lbs.	.110	2.79	.015	0.38	Natural	E	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in.	mm	Nom. Thickness in.	mm	Color	Mil-Spec Finish	Standard Spool
808032B	2	80 lbs.	.110	2.79	.015	0.38	Black	E	250 yds.
805030W	3	50 lbs.	.085	2.16	.014	0.36	Natural	A	500 yds.
805030B	3	50 lbs.	.085	2.16	.014	0.36	Black	A	500 yds.
805036W	3	50 lbs.	.085	2.16	.014	0.36	Natural	B	500 yds.
805036B	3	50 lbs.	.085	2.16	.014	0.36	Black	B	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in.	mm	Nom. Thickness in.	mm	Color	Mil-Spec Finish	Standard Spool
805040W	3	50 lbs.	.085	2.16	.014	0.36	Natural	C	500 yds.
805040B	3	50 lbs.	.085	2.16	.014	0.36	Black	C	500 yds.
805032W	3	50 lbs.	.085	2.16	.014	0.36	Natural	E	500 yds.
805032B	3	50 lbs.	.085	2.16	.014	0.36	Black	E	500 yds.
802530W	4	25 lbs.	.060	1.52	.012	0.30	Natural	A	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in.	mm	Nom. Thickness in.	mm	Color	Mil-Spec Finish	Standard Spool
802530B	4	25 lbs.	.060	1.52	.012	0.30	Black	A	500 yds.
802534W	4	25 lbs.	.060	1.52	.012	0.30	Natural	B	500 yds.
802534B	4	25 lbs.	.060	1.52	.012	0.30	Black	B	500 yds.
802540W	4	25 lbs.	.060	1.52	.012	0.30	Natural	C	500 yds.
802540B	4	25 lbs.	.060	1.52	.012	0.30	Black	C	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in.	mm	Nom. Thickness in.	mm	Color	Mil-Spec Finish	Standard Spool
802532W	4	25 lbs.	.060	1.52	.012	0.30	Natural	E	500 yds.
802532B	4	25 lbs.	.060	1.52	.012	0.30	Black	E	500 yds.
801530W	5	15 lbs.	.050	1.27	.010	0.25	Natural	A	500 yds.
801530B	5	15 lbs.	.050	1.27	.010	0.25	Black	A	500 yds.
801536W	5	15 lbs.	.050	1.27	.010	0.25	Natural	B	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in.	mm	Nom. Thickness in.	mm	Color	Mil-Spec Finish	Standard Spool
801536B	5	15 lbs.	.050	1.27	.010	0.25	Black	B	500 yds.
801540W	5	15 lbs.	.050	1.27	.010	0.25	Natural	C	500 yds.
801540B	5	15 lbs.	.050	1.27	.010	0.25	Black	C	500 yds.
801532W	5	15 lbs.	.050	1.27	.010	0.25	Natural	E	500 yds.
801532B	5	15 lbs.	.050	1.27	.010	0.25	Black	E	500 yds.

Finishes and Coatings: A-Natural Finish* B-Wax C-Synthetic Rubber or Elastomer E-Vinyl or Synthetic Resin *No additional coating.