



Lacing Tape and Twine

MILITARY GRADE POLYESTER LACING TAPE

*MIL-T-43435B, TYPE II

DESCRIPTION

• Construction: Flat braid manufactured from high tenacity, continuous filament yarn.

CHARACTERISTICS

• Temperature Range: -73 to +177C.

FEATURES & APPLICATIONS

• For use in bundling military or commercial wire harnesses.
 *Polyester has good tensile strength and resists acids, abrasion, flame and fungus.

APPROVALS

• MIL-T-43435B, Type II.

Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
813560W	1	135 lbs.	.200 5.08	.016 0.41	Natural	A	250 yds.
813560B	1	135 lbs.	.200 5.08	.016 0.41	Black	A	250 yds.
813562W	1	135 lbs.	.200 5.08	.016 0.41	Natural	B	250 yds.
813562B	1	135 lbs.	.200 5.08	.016 0.41	Black	B	250 yds.
813566W	1	135 lbs.	.200 5.08	.016 0.41	Natural	C	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
813566B	1	135 lbs.	.200 5.08	.016 0.41	Black	C	250 yds.
813558W	1	135 lbs.	.200 5.08	.016 0.41	Natural	E	250 yds.
813558B	1	135 lbs.	.200 5.08	.016 0.41	Black	E	250 yds.
808060W	2	80 lbs.	.110 2.79	.015 0.38	Natural	A	250 yds.
808060B	2	80 lbs.	.110 2.79	.015 0.38	Black	A	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool
808062W	2	80 lbs.	.110 2.79	.015 0.38	Natural	B	250 yds.
808062B	2	80 lbs.	.110 2.79	.015 0.38	Black	B	250 yds.
808066W	2	80 lbs.	.110 2.79	.015 0.38	Natural	C	250 yds.
808066B	2	80 lbs.	.110 2.79	.015 0.38	Black	C	250 yds.

808058W	2	80 lbs.	.110	2.79	.015	0.38	Natural	E	250 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool		
808058B	2	80 lbs.	.110	2.79	.015	0.38	Black	E	250 yds.
805060W	3	50 lbs.	.085	2.16	.014	0.36	Natural	A	500 yds.
805060B	3	50 lbs.	.085	2.16	.014	0.36	Black	A	500 yds.
805062W	3	50 lbs.	.085	2.16	.014	0.36	Natural	B	500 yds.
805062B	3	50 lbs.	.085	2.16	.014	0.36	Black	B	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool		
805066W	3	50 lbs.	.085	2.16	.014	0.36	Natural	C	500 yds.
805066B	3	50 lbs.	.085	2.16	.014	0.36	Black	C	500 yds.
805058W	3	50 lbs.	.085	2.16	.014	0.36	Natural	E	500 yds.
805058B	3	50 lbs.	.085	2.16	.014	0.36	Black	E	500 yds.
802560W	4	25 lbs.	.060	1.52	.012	0.30	Natural	A	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool		
802560B	4	25 lbs.	.060	1.52	.012	0.30	Black	A	500 yds.
802562W	4	25 lbs.	.060	1.52	.012	0.30	Natural	B	500 yds.
802562B	4	25 lbs.	.060	1.52	.012	0.30	Black	B	500 yds.
802566W	4	25 lbs.	.060	1.52	.012	0.30	Natural	C	500 yds.
802566B	4	25 lbs.	.060	1.52	.012	0.30	Black	C	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool		
802558W	4	25 lbs.	.060	1.52	.012	0.30	Natural	E	500 yds.
802558B	4	25 lbs.	.060	1.52	.012	0.30	Black	E	500 yds.
801560W	5	15 lbs.	.050	1.27	.010	0.25	Natural	A	500 yds.
801560B	5	15 lbs.	.050	1.27	.010	0.25	Black	A	500 yds.
801562W	5	15 lbs.	.050	1.27	.010	0.25	Natural	B	500 yds.
Part Number	Mil-Spec Size	Strength (Min.)	Nom. Width in. mm	Nom. Thickness in. mm	Color	Mil-Spec Finish	Standard Spool		
801562B	5	15 lbs.	.050	1.27	.010	0.25	Black	B	500 yds.
801566W	5	15 lbs.	.050	1.27	.010	0.25	Natural	C	500 yds.
801566B	5	15 lbs.	.050	1.27	.010	0.25	Black	C	500 yds.
801558W	5	15 lbs.	.050	1.27	.010	0.25	Natural	E	500 yds.
801558B	5	15 lbs.	.050	1.27	.010	0.25	Black	E	500 yds.

Finishes and Coatings: A-Natural Finish* B-Wax C-Synthetic Rubber or Elastomer E-Vinyl or Synthetic Resin *No additional coating.