


Product Catalog

For Web Assistance: (800) 323-0198



Company Profile
and History



Product
Quote Form



Find a
Distributor



Contact Us

Product Index



Hookup Wire	Braided Stranded Copper Wire	Multiconductor	Tubing	Coaxial Cable
-------------	------------------------------	----------------	--------	---------------

Check the Items You'd Like to Add to Your Quote or Order

UL and CSA Multi-Rated Hookup Wire

POLYVINYLCHLORIDE INSULATION (105C, 300 VOLTS)

*PRIMARY RATINGS - UL STYLES 1569, 1007

Standard Putups:

- 500ft.
- 1000ft.
- bulk.

See color chart 8 in
Technical Section.
Consult factory for
availability of
other colors and
color
combinations.

DESCRIPTION

Conductors: Fully annealed stranded, solid or topcoated tinned copper per ASTM standards.

Insulation: Color coded PVC.

CHARACTERISTICS

Temperature: 80C, 90C, or 105C.

Voltage Rating: 300 Volts. (Tag may also indicate 600 Volt peak for electronic use only).

FEATURES & APPLICATIONS

For internal wiring of appliances or electronic and electrical equipment where not subjected to movement or mechanical damage.

APPROVALS

UL: 1569: 105C - 300V 1497: 80C - 300V (26-16 AWG) 1007: 80C - 300V (28-16 AWG) 1581: 80C - 300V (15-10 AWG) 1039: 80C - 300V (28-16 AWG 7 strands only)

CSA: Type TR-64.

Recognized under the components program of Underwriters' Laboratories, Inc. Authorized by Canadian Standards Association to represent as CSA Certified. Passes VW-1 and FT1 Vertical Flame Tests. Surface printed.

	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Color Code
	892807	28	7/36	.015 0.38	.016 0.41	.047 1.19	0-9
	892601	26	Solid	.016 0.41	.016 0.41	.048 1.22	0-9
	892607	26	7/34	.019 0.48	.016 0.41	.051 1.30	0-9
	892401	24	Solid	.020 0.51	.016 0.41	.052 1.32	0-9
	892407	24	7/32	.024 0.61	.016 0.41	.056 1.42	0-9
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Color Code
	892407T	24	7/32	.024 0.61	.016 0.41	.056 1.42	0-9
	892419	24	19/36	.024 0.61	.016 0.41	.056 1.42	0-9
	892201	22	Solid	.025 0.64	.016 0.41	.057 1.45	0-9
	892207	22	7/30	.030 0.76	.016 0.41	.062 1.57	0-9
	892207T	22	7/30	.031 0.79	.016 0.41	.063 1.60	0-9
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Color Code
	892219	22	19/34	.031 0.79	.016 0.41	.063 1.60	0-9
	892001	20	Solid	.032 0.81	.016 0.41	.064 1.63	0-9

	892007	20	7/28	.038 0.97	.016 0.41	.070 1.78	0-9
	892010	20	10/30	.037 0.94	.016 0.41	.069 1.75	0-9
	892010T	20	10/30	.039 0.99	.016 0.41	.071 1.80	0-9
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Color Code
	892019	20	19/32	.040 1.02	.016 0.41	.072 1.83	0-9
	891801	18	Solid	.040 1.02	.016 0.41	.072 1.83	0-9
	891816	18	16/30	.045 1.14	.016 0.41	.077 1.96	0-9
	891816T	18	16/30	.045 1.14	.016 0.41	.077 1.96	0-9
	891819	18	19/30	.050 1.27	.016 0.41	.082 2.08	0-9
	Part Number	AWG	Stranding	Nom. Dia. of Conductor in. mm	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Color Code
	891626	16	26/30	.058 1.47	.016 0.41	.090 2.29	0-9
	891441	14	41/30	.071 1.80	.016 0.41	.103 2.62	0-9
	891265	12	65/30	.089 2.26	.016 0.41	.121 3.07	0-9
	891000	10	105/30	.109 2.77	.016 0.41	.141 3.58	0-9

T-Indicates topcoat conductor

If you wish to add the products to your quote or complete your quote check one of these buttons

[Home](#) | [Profile](#) | [Catalog](#) | [Quote Form](#) | [Representatives](#) | [Contact](#)

Copyright 1997-2001, Dearborn Wire and Cable, Inc.