

Hookup Wire

Braided Stranded Copper Wire

Multiconductor

Tubing

Coaxial Cable

Premier Marine Wire and Cable

PREMIER BATTERY MARINE CABLE

Standard Putups:

- 100 ft.
- 500 ft.
- 1000 ft.

See color chart 8 in Technical Section. Consult factory for availability of other colors and color combinations.

DESCRIPTION

- Conductors: Extra-flexible corrosion-resistant tinned copper Type 3 marine stranding for longer life.
- Insulation: Elastoplex (TM), 105C insulation.

CHARACTERISTICS

- Temperature: 105C.
- Voltage Rating: 50 Volts DC, 600 Volts AC.
- Resistant To: Harsh marine environment, including salt water, oil, and gas.

FEATURES & APPLICATIONS

- For use in marine engine wiring assemblies as well as other electrical components.

APPROVALS

- UL: Standard 1426
- CSA: AWM I A/B and TEW.
- UL Listed Standard 1426 Boat Cable. SAE J1127 (8 AWG J1128), SAE J378. AWM Style 1283 & 1284. CSA AWM I A/B and CSA TEW. Type SGT. ABYC and Coast Guard requirements. Passes VW-1 Vertical Flame Test.

Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm		Nom. O.D. in. mm		Approx. Ship WT./MFT.	Color Code
PBM0830	8	168/30	.060	1.52	.300	7.62	71.0	0,2,5,9
PBM0630	6	266/30	.060	1.52	.344	8.73	109.0	0,2,5,9
PBM0430	4	420/30	.065	1.65	.400	10.16	161.0	0,2
PBM0230	2	665/30	.065	1.65	.469	11.91	254.0	0,2
PBM0130	1	836/30	.080	2.03	.545	13.84	312.0	0,2
Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm		Nom. O.D. in. mm		Approx. Ship WT./MFT.	Color Code
PBM0001	1/0	1064/30	.080	2.03	.593	15.06	383.0	0,2
PBM0002	2/0	1323/30	.080	2.03	.652	16.56	464.0	0,2
PBM0003	3/0	1666/30	.080	2.03	.703	17.85	612.0	0,2
PBM0004	4/0	2107/30	.080	2.03	.758	19.25	765.0	0,2

ElastoPlex(TM) is a trademark of Dearborn/CDT.