



Company Profile
and History



Product
Quote Form



Find a
Distributor



Contact Us

Product Index



Hookup Wire

Braided Stranded Copper Wire

Multiconductor

Tubing

Coaxial Cable

Check the Items You'd Like to Add to Your Quote or Order

Premier Marine Wire and Cable

PREMIER PRIMARY MARINE WIRE

Standard Putups: • 100 ft. • 500 ft. • 1000 ft. See color chart 8 in Technical Section.	DESCRIPTION • Conductors: Extra-flexible corrosion-resistant tinned copper Type 3 marine standing for longer life. • Insulation: Polyvinylchloride, 105C insulation.			FEATURES & APPLICATIONS • For use in marine engine wiring assemblies as well as other applications.					
	CHARACTERISTICS • Temperature: 105C. • Voltage Rating: 50 Volts DC, 600 Volts AC. • Resistant To: Harsh marine environment, including salt water, oil, and gas.			APPROVALS • UL: Standard 1426 • CSA: AWM I A/B. • UL Standard 1426 Boat Cable. SAE J378B, J1128 Type GPT (18-8 AWG). AWM Styles 1015, 1230, 1028. CSA AWM I A/B. ABYC and Coast Guard requirements. NMMA.					
	Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm		Nom. O.D. in. mm		Approx. Ship WT/MFT.	Color Code
	PPM1830	18	16/30	.031	0.79	.109	2.76	11.0	0-9
	PPM1630	16	26/30	.031	0.79	.122	3.09	14.0	0-9
	PPM1430	14	41/30	.031	0.79	.136	3.45	20.0	0-9
	PPM1230	12	65/30	.031	0.79	.153	3.88	29.5	0-9
	PPM1030	10	105/30	.031	0.79	.173	4.39	42.0	0-9
	Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm		Nom. O.D. in. mm		Approx. Ship WT/MFT.	Color Code
	PPM0830	8	168/30	.048	1.22	.256	6.50	67.0	0,2,3,5

18 AWG is recognized by UL as Style 1230. When used as a jacketed cable (two or more), it meets the requirements of UL Boat Cable Standard 1426. 12 AWG also available Yellow with Red Stripe, Part No. PPM1230-42.

If you wish to add the products to your quote or complete your quote check one of these buttons