

Hookup Wire

Braided Stranded Copper Wire

Multiconductor

Tubing

Coaxial Cable

## Premier Marine Wire &amp; Cable

## Premier Round Marine Cable

## Standard

## Putups:

- 100 ft.
- 500 ft.
- 1000 ft.

**DESCRIPTION**

■ Conductors: Annealed Tinned Copper Corrosion-Resistant Conductors. Extra-Flexible Type 3 Marine Stranding For Longer Life.

■ Jacket: White Flame-REtardant VW-1 Rated Polyvinylchloride Jacket.

**CHARACTERISTICS**

- Temperature: 105C.
- Voltage Rating: 600 Volts AC.

**APPROVALS**

- UL Listed Standard 1426 Boat Cable.

Part Number	No. of Conductors	AWG	Stranding	Nom. Insulation Thickness in. mm	Approx. O.D. in. mm	Approx. Ship WT/MFT
PRM1602	2	16	26/30	.031 0.79	.330 8.38	48.0
PRM1603	3	16	26/30	.031 0.79	.354 8.99	73.0
PRM1604	4	16	26/30	.031 0.79	.374 9.50	86.0
PRM1402	2	14	41/30	.031 0.79	.375 9.53	59.9
PRM1403	3	14	41/30	.031 0.79	3.81 9.68	99.0
Part Number	No. of Conductors	AWG	Stranding	Nom. Insulation Thickness in. mm	Approx. O.D. in. mm	Approx. Ship WT/MFT
PRM1404	4	14	41/30	.031 0.79	.415 10.54	128.0
PRM1202	2	12	65/30	.031 0.79	.413 10.49	81.7
PRM1203	3	12	65/30	.031 0.79	.415 10.54	168.0
PRM1204	4	12	65/30	.031 0.79	.460 11.68	224.0
PRM1003	3	10	105/30	.031 0.79	.482 12.24	219.0