

Description:

This product is designed for use in ESD controlled areas where there are ESDsensitive devices. This product is constructed out of 6 mil, clear, permanently dissipative polyethylene film. Drawing protectors are designed to provide static control packaging for holding engineering drawings or other large documents. This product meets or exceeds the requirements of MIL-B-81705C, Type II.

Amine-free.

N-Octanoic acid free. Humidity independent. Does not promote corrosion. Has no measurable outgassing.

Electrical Properties:

Static Decay: Surface Resistivity: < 2.0 sec. 10¹⁰ - 10¹² ohms

Specifications:

Polycarbonate haze: Corrosivity: Melt Index: Density: Dart impact: Coefficient of friction: 1% secant modulus: Stiffness:

Negligible Nealibible .050 gm/10 min. 0.923 gm/cc 230 gms 0.50 MD 24,000 psi MD 25,000 psi

per FTMS 101C, Method 4046 per ASTM D-257

72 hr contact per FTMS 101C. Method 3005 per ASTM D-1238 per ASTM D-1505 per ASTM D-1709 per ASTM D-1894 per ASTM D-882 per ASTM D-882

A. B size drawing holder will hold up to an 11" x 17" sheet size. Wording across bottom area:



07456 / 47123 Made in America Descolndustries.com



Made in America

Drawing Protector, Statfree®, 6 Mil



Opening

11-1/4"

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449 DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DATE: DRAWING NUMBER June 07456 2007

17-1/2"