

Statguard® Conductive Acrylic Latex Paint



Light Grey

Dark Grey

**An Effective Alternative to Conductive
Floor Mats & Tiles**

Features and Benefits:

- **RTT 10⁴ - 10⁶ ohms per ESD-S7.1**
 - Conductive - able to remove electrostatic charges to ground
 - Exceeds ANSI/ESD S20.20 minimum recommended technical requirements of < 1 x 10⁹ ohms for ESD Protected Flooring and suitable for ESD protective flooring
 - Can be component in Flooring - Footwear System as primary grounding method (<3.5 x 10⁷ohms per ESD STM 97.1)
- **Areas greater than 20 square feet do not require expensive grounding grids or wires; Static Charge Decay: dissipates 5000 volts to zero in <0.01 sec per FTMS 101C/4046**
Can replace ESD floor mats in electronics, manufacturing, assembly, and test areas protecting ESD susceptible items
- **Adheres to floors, walls, or wood furniture**
Provides ESD protective surface on concrete and epoxy floors and in places which are difficult to protect
- **Excellent wear and durability**
Excellent value providing long-life
- **Apply via rolling or spraying**
Productive application and maintenance; easy cleanup
- **Two colors to choose from**
Grey hides dirt better in most applications; Light Grey brightens up factory area
- **RTT: 10⁴ - 10⁶ ohms per ESD S7.1 @ 50% R.H.**
- **Coverage: 300-400 sq. ft/gallon**
Excellent value
- **This product has been certified to meet the RoHS requirement.**
- **Made in America**

P/N	Description
10408	1 Gallon Pail, Grey
10409	5 Gallon Pail, Grey
10410	5 Gallon Pail, Light Grey

Note: ESD protected flooring requires a path-to-ground from carts or equipment & ESD footwear on personnel to remove electrostatic charges.

RTT: $<10^5$ ohms per ASTM D257

Static Charge Decay: 5000 volts to zero in <0.01 sec per FTMS 101C/4046

Technical Bulletin [TB-7001](#)

[Desco Floor Care Calculator](#) - Click here to choose your Statguard® or Statfree® floor care maintenance program and determine the annual budget and cost per sq/ft. This tool walks you through the choices of an annual floor care maintenance program. The calculator produces a list of products and quantity needed for the chosen maintenance and floor area entered.



West Coast: 3651 Walnut Ave., Chino, CA 91710
Phone: (909) 627-8178 Fax: (909) 627-7449

East Coast: 90 Hudson Road, Canton, MA 02021
Phone: (781) 821-8370 Fax: (781) 575-0172

[Home](#) [Promotions](#) [Products](#) [Technical](#) [Services](#) [Contact](#) [ESD Information](#)

Copyright © 2005 Desco Industries, Inc. All Rights Reserved