

Statguard® Dissipative Floor Finish



Durable, Static Control Floor Coating with a High Gloss Finish



Item #10500 Statguard® label included at no charge with 2.5 and 5 gallon Cube Bag-in-Box

The 10500 Statguard® Label is used to identify a floor as "ESD Protective" and meets ANSI/ESD S20.20


Features

Features and Benefits:

- **Non-tribocharging**
Limits charge generation when walking - <100 volts per ANSI/ESD S20.20
- **Static dissipative**
With ESD footwear, removes the charge off your body
- **Can be applied on many hard surfaces or sealed floors including vinyl, VCT, linoleum, rubber, epoxy, acrylic paint, and concrete**
Converts a non-ESD floor to an ESD floor
- **UL classified for slip resistance only**
Ensures worker safety and mitigates user's liability exposure
- **18% solids**
Easy to apply; improves productivity
- **Cross-linked polymer**
Produces high-gloss, durable finish
- **Low humidity formulation**
Provides greater durability in all humidity environments
- **Bag-in-box packaging**
[Click here to see storage, dispensing, and savings benefits](#)
- **RTT 10⁷ ohms per ESD S7.1 @50% R.H.**
- **Made in America**

P/N	Description
10511	Statguard® Floor Finish, 2.5 gallon cube bag-in-box
10512	Statguard® Floor Finish, 5 gallon cube bag-in-box
10520	Statguard® Floor Finish, 55 Gallon Drum
10554	Statguard® LH Floor Finish, 2.5 gallon cube bag-in-box
10556	Statguard® LH Floor Finish, 5 gallon cube bag-in-box

Important Safety Feature



Classified by UL as to slip resistance only, Statfree® and Statguard® provide superior electrical properties along with a safe walking surface. Underwriters Laboratory has evaluated Statfree® and Statguard® and tested them to their slip resistance standards. To ensure employee safety and to mitigate user's liability exposure, it is important to use floor finish that has been successfully tested for slip resistance, and is properly applied and maintained.

RTT: 10⁷ ohms per ESD S4.1 @ 50% R.H. pH: 8.9
Coverage: 2,000-2,500 sq. ft/gallon Solids: 18%
Density: 8.4 lbs./gal Water soluble

Technical Bulletin [TB-2088](#)

[Desco Floor Care Calculator](#) - Click here to choose your Statguard® or Statfree® floor care maintenance program and determine the annual budget and cost per sq/ft. This tool walks you through the choices of an annual floor care maintenance program. The calculator produces a list of products and quantity needed for the chosen maintenance and floor area entered.



West Coast: 3651 Walnut Ave., Chino, CA 91710
Phone: (909) 627-8178 Fax: (909) 627-7449

East Coast: 90 Hudson Road, Canton, MA 02021
Phone: (781) 821-8370 Fax: (781) 575-0172

[Home](#) [Promotions](#) [Products](#) [Technical](#) [Services](#) [Contact](#) [ESD Information](#)

Copyright © 2005 Desco Industries, Inc. All Rights Reserved