



Series 04, 44 Illumination

Illumination Type	General Data	Electrical Ratings		Luminous Intensity	Average Life (hours)	Former P/N	Part Number	
		Volts	Milliamps					
Incandescent T-3 1/4 bayonet base For higher voltages use lamp transformer or resistor/capacitor block.	Clear	6	200	0.30 mscp	15,000	700-000.0	10-1406.1369	
	Clear	12	100	0.25 mscp	10,000	700-000.1	10-1409.1329	
	Clear	24	50	0.32 mscp	5,000	700-000.2	10-1412.1279	
	Clear	36	56	0.50 mscp	5,000	700-000.3	10-1416.1289	
	Clear	48	42	0.50 mscp	5,000	700-000.4	10-1419.1249	
	Clear	60	33	0.40 mscp	3,000	700-000.5	10-1420.1219	
	Clear	110	22	0.30 mscp	4,000	700-000.6	10-1422.1179	
	Clear	130	20	0.10 mscp	7,000	700-000.7	10-1424.1179	
	Neon, T-3 1/4, with integral resistor 	Amber	230	1.5	100 mlm	25,000	700-001.1	10-7425.2022
		Amber	400	0.8	100 mlm	25,000	700-001.2	10-7426.2012
8-chip		6 DC	80	50/30/30 mcd**	50,000	700-002.0	10-6406.331	
8-chip		12 DC	40	50/30/30 mcd**	50,000	700-002.1	10-6409.324	
Multi-chip LED, T-3 1/4, with integral resistor 	8-chip	24 DC	19	50/30/30 mcd**	50,000	700-002.2	10-6412.316	
	8-chip	48 DC	16	50/30/30 mcd**	50,000	700-002.4	10-6419.315	

Select color: 2 = Red, 4 = Yellow, 5 = Green ** mcd rating for Red/Yellow/Green

Series 18 Illumination