



Connector ①



Table 15. Connector

	For Use with...	Pkg. Qty.	Catalog Number	Price U.S. \$ ②
	XTRE(C)10B	50	XTCEXCNC	1.10
	XTRM10A	50	XTMCXCN	1.10

- ① For mechanically arranging contactors in combinations. Distance between contactors is 0 mm.
- ② Price listed is for a quantity of one (1). Orders must be placed in multiples of package quantity listed.

Mechanical Interlock ③

Table 16. Mechanical Interlock

	For Use with...	Pkg. Qty.	Catalog Number	Price U.S. \$ ④
	XTRE10B...	5	XTCEXMLB	20.30
	XTRM10A...	5	XTMCXML	19.20





- ③ For two contactors with AC or DC operated magnet system which are horizontally or vertically mounted. For B frame, mechanical lifespan is 2.5×10^6 operations and the distance between contactors is 0 mm.
- ④ Price listed is for a quantity of one (1). Orders must be placed in multiples of package quantity listed.

Electronic Timer Modules



Front (Top) mounted timer modules for use with XTRE10B control relays. Can not be combined with top mount auxiliary contacts, XTCEXF_C_.

Table 17. Electronic Timer Modules for XTRE

Voltage	Contact Sequence	Timing Range	For Use with...	Pkg. Qty.	Catalog Number	Price U.S. \$
On-Delayed						
24V AC/DC		0.05 – 1 s	XTRE10B_	1	XTCEXTEEC11T	179.00
100 – 130V AC		0.5 – 10 s			XTCEXTEEC11A	179.00
200 – 240V AC		15 – 100 s			XTCEXTEEC11B	179.00
Off-Delayed						
24V AC/DC		0.05 – 1 s	XTRE10B_	1	XTCEXTED1C11T	198.00
100 – 130V AC		0.5 – 10 s			XTCEXTED1C11A	198.00
200 – 240V AC					XTCEXTED1C11B	198.00
24V AC/DC			5 – 100 s	XTCEXTED10C11T	198.00	
100 – 130V AC		XTCEXTED10C11A		198.00		
200 – 240V AC		XTCEXTED10C11B		198.00		
24V AC/DC		1 – 30 s	XTRE10B_	1	XTCEXTED100C11T	198.00
100 – 130V AC					XTCEXTED100C11A	198.00
200 – 240V AC					XTCEXTED100C11B	198.00
Star-Delta						
24V AC/DC		1 – 30 s	XTRE10B_	1	XTCEXTEYC20T	198.00
100 – 130V AC					XTCEXTEYC20A	198.00
200 – 240V AC					XTCEXTEYC20B	198.00
Sealable Shroud						
	Transparent sealable shroud used to protect electronic timer modules from unwanted access.		XTCEXTEE, XTCEXTED, XTCEXTEY	1	XTCEXTESHRD	12.00