

# 3900 Series

# Tubeaxial

## 92x92x25mm



- AC fans with internal rotor shaded-pole motor. Impedance protected against overloading.
- Metal fan housing, impeller of mineral-reinforced plastic PA.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Mounting from either face using four 4.3 mm holes.
- Electrical connection via 2 flat pins 2.8 x 0.5 mm.
- Fan housing with ground lug for screw M4.
- UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	Curve	CFM @ 0	VAC	Hertz	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Speed (RPM)	Features	Wgt. (lbs)
3900L	4	23.0	115	60	5	27	80	Sintec	1850	Terminals	0.62
3906L	4	23.0	115	60	5	27	80	Ball	1850	Terminals	0.62
3900M	5	31.2	115	60	5	34	80	Sintec	2600	Terminals	0.62
3906M	5	31.2	115	60	5	34	80	Ball	2600	Terminals	0.62
3900	6	41.2	115	60	9	40	80	Sintec	3150	Terminals	0.62
3906	6	41.2	115	60	9	40	80	Ball	3150	Terminals	0.62
3950L	1	18.2	230	50	6	24	80	Sintec	1550	Terminals	0.62
3956L	1	18.2	230	50	6	24	80	Ball	1550	Terminals	0.62
3950M	2	26.5	230	50	6	29	80	Sintec	2150	Terminals	0.62
3956M	2	26.5	230	50	6	29	80	Ball	2150	Terminals	0.62
3950	3	34.7	230	50	11	35	80	Sintec	2650	Terminals	0.62
3956	3	34.7	230	50	11	35	80	Ball	2650	Terminals	0.62

