

# International Linear Open Frame Power Supplies

## Single Output

### Features:

- Part Number: SS12-3.4  
.....Output: 12V 3.4A
- Part Number: SS5-6/OVP  
.....Output: 5V 6A
- Part Number: SS24-2.4  
.....Output: 24V 2.4A
- Multiple AC Input Capabilities - 60 Hz. or 50 Hz. - (derate 10% for 50 Hz. applications)
- Full rated output from 0° C to +50° C
- Storage Temperature: -20° C to 85° C
- Adjustable output - +/-5% minimum.
- Output Regulation: +/- 0.05% for 50% load change
- Output Ripple/noise (Vp-p): 5 mV max
- Line Regulation : + -0.05% for AC 10% change
- Remote sense provided on all models, 3 Amps and above, Open sense lead protection built in.
- Reverse Voltage Protection: provided on all outputs.
- Transient Response: 50 us at 50% load change.
- Hold up time: Less than 1 ms at nominal input typical load
- Industry standard outline and mounting
- Worldwide safety approvals - UL/CSA/EN60950
- Meets FCC class B, CISPR 22 class B
- OVP: built in on all 5 volt outputs; optional on others
- Overload protection: Automatic current limit/foldback.
- Temperature Coefficient: +/-0.03%/°C max.
- Warranty - 3 years



### C CASE



