Product Detail



Product Line: Johnson (Click for customer service)

Part Number: 105-0604-001

Description: Tip Jack - Insulated Deluxe

Product Family: TIP JACK

Body Material: Nylon 6/6 per ASTM D4066

Breakdown Voltage:

5700 Vrms min.

Color / Finish: Green

Contact Material: Beryllium copper over brass

Contact Finish: Silver

Contact

Termination:

Solder

Current: 10 amps

Description: Insulated Deluxe For Use With: .080 (2.00) Tip Plug Panel Thickness: Up to .437 (11.10)

RoHS Compliant: Yes

20070523-1523

Tip Jack Insulated Deluxe

SPECIFICATIONS

Contact: Brass per QQ-B-626D with wrap around beryllium copper spring per QQ-C-533

Finish: Silver

Body: Nylon 6/6 per ASTM D4066

Hardware: Nickel plated nut (unassembled)

Body Thread Stripping Torque: 0.4 lb. in (4.5 kg. cm.)


Panel Thickness: Up to .437 (11.10)

RATINGS

Current: 10 amps

Breakdown Voltage: 5700 Vrms minimum † **Contact Resistance**: 0.010 ohms maximum

Contact-To-Panel C: 2 pF nominal



-.750 (19.04)-

INCHES (MILLIMETERS)
CUSTOMER DRAWINGS AVAILABLE UPON REQUEST

SILVER PLATING	
PART NO.	COLOR
105-0604-001	Green

For Standard Tip Plug: .080 (2.00) Diameter FEATURES:

- · Machined contact with turret terminal
- Hex socket head .188 (4.77) for ease in mounting
- Closed entry blocks access of probes greater than .085 (2.16)
- Nylon UL approved for self extinguishing