


## 8304 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232 Applications



### Description:

22 AWG stranded (7x30) tinned copper conductors, semi-rigid PVC insulation, twisted pairs, overall Beldfoil® (100% coverage) + tinned copper braid shield (65% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material
4	22	7x30	TC - Tinned Copper

#### Insulation

##### Insulation Material:

Insulation Material
S-R PVC - Semi-Rigid Polyvinyl Chloride

#### Outer Shield

##### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cabling

Overall Nominal Diameter: 0.320 in.

#### Pair

##### Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue

##### Pair Lay Length & Direction:

Lay Length (in.)	Twists/ft. (twist/ft)
1.000	12.000

### Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +80°C
UL Temperature Rating:	80°C (UL AWM Style 2464)
Bulk Cable Weight:	58 lbs/1000 ft.
Max. Recommended Pulling Tension:	102 lbs.
Min. Bend Radius (Install)/Minor Axis:	3.200 in.

## 8304 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232 Applications

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
AWM Specification:	UL Style 2464 (300 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

C(UL) Flame Test:	FT4
-------------------	-----

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)
70

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
35

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
63

#### Nominal Velocity of Propagation:

VP (%)
60

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
15.0

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
4.9

#### Max. Operating Voltage - UL:

Voltage
300 V RMS (UL AWM Style 2464)

#### Max. Recommended Current:

Current
2.1 Amps per conductor @ 25°C

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8304 060100	100 FT	6.700 LB	CHROME		4 #22 PR SHLD PVC
8304 0601000	1,000 FT	65.000 LB	CHROME	C	4 #22 PR SHLD PVC

ENGLISH MEASUREMENT VERSION

---

## 8304 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232 Applications

8304 060500	500 FT	32.500 LB	CHROME	C	4 #22 PR SHLD PVC
-------------	--------	-----------	--------	---	-------------------

**Notes:**

C = CRATE REEL PUT-UP.

## Introduction

Belden® paired cable products are manufactured in a variety of gage sizes, dimensions, insulation materials, shielding configurations, and jacketing materials including Plenum and High-Temperature versions to meet the technical requirements of many different types of systems.

Paired cables allow balanced signal transmission, which results in lower crosstalk through common mode rejection. Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables.

As an aid to proper cable selection, both the suggested working voltages and the maximum temperature ratings are indicated for each applicable paired cable selection.



Most of our paired cables are available from stock. Many of these are available off the shelf from distributors. If you have a new or unusual application or you cannot find a paired cable in this catalog section that meets your technical requirements, contact Technical Support at 1-800-BELDEN-1.

### Paired Cables Packaging

Belden's unique UnReel® cable dispenser is available for many of the paired cable products listed in this section. The letter "U" before the specified put-up length denotes UnReel packaging.

# Overall Foil/Braid Shield

## Low-Capacitance Computer Cables for EIA RS-232 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
<b>22 AWG Stranded (7x30) Tinned Copper Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage)</b>																		
<b>Semi-rigid PVC Insulation • Chrome PVC Jacket</b>																		
UL AWM Style 2464 (300V 80°C)  Z-Fold®	<b>8302</b>	NEC: CMG CEC: CMG FT4	2	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	4.5 19.0 41.0	2.0 8.6 18.6	15.0Ω/M' 49.2Ω/km	5.7Ω/M' 18.7Ω/km	.260 6.60	70	60%	40	131	72	236	
	<b>8303</b>	NEC: CMG CEC: CMG FT4	3	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	5.2 25.5 48.0	2.4 11.6 21.8	15.0Ω/M' 49.2Ω/km	6.2Ω/M' 20.3Ω/km	.270 6.86	70	60%	35	115	63	207	
	<b>8304</b>	NEC: CMG CEC: CMG FT4	4	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.7 32.5 65.0	3.0 14.7 29.5	15.0Ω/M' 49.2Ω/km	4.9Ω/M' 16.1Ω/km	.320 8.13	70	60%	35	115	63	207	
	<b>8305</b>	NEC: CMG CEC: CMG FT4	5	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	7.2 35.0 67.0	3.3 15.9 30.4	15.0Ω/M' 49.2Ω/km	4.8Ω/M' 15.7Ω/km	.322 8.18	70	60%	35	115	63	207	
	<b>8306</b>	NEC: CMG CEC: CMG FT4	6	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.0 39.5 79.0	3.6 18.0 35.8	15.0Ω/M' 49.2Ω/km	5.0Ω/M' 16.4Ω/km	.348 8.84	70	60%	35	115	63	207	
	<b>8307</b>	NEC: CMG CEC: CMG FT4	7	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.6 42.0 85.0	3.9 19.0 38.6	15.0Ω/M' 49.2Ω/km	5.0Ω/M' 16.4Ω/km	.348 8.84	70	60%	35	115	63	207	
	<b>8308</b>	NEC: CMG CEC: CMG FT4	8	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	10.4 50.0 101.0	4.7 22.7 46.0	15.0Ω/M' 49.2Ω/km	4.4Ω/M' 14.4Ω/km	.384 9.75	70	60%	35	115	63	207	
	UL AWM Style 2464 (300V 80°C) 	<b>8310</b>	NEC: CMG CEC: CMG FT4	10	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	11.1 60.5 121.0	5.0 27.4 54.9	15.0Ω/M' 49.2Ω/km	4.1Ω/M' 13.4Ω/km	.440 11.18	70	60%	35	115	63	207
		<b>8312</b>	NEC: CMG CEC: CMG FT4	12	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	12.9 72.0 140.0	5.9 32.8 63.8	15.0Ω/M' 49.2Ω/km	4.2Ω/M' 13.8Ω/km	.455 11.56	70	60%	35	115	63	207
		<b>8315</b>	NEC: CMG CEC: CMG FT4	15	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	15.7 85.5 167.0	7.1 39.0 76.1	15.0Ω/M' 49.2Ω/km	3.8Ω/M' 12.5Ω/km	.502 12.75	70	60%	35	115	63	207
		<b>8318</b>	NEC: CMG CEC: CMG FT4	18	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	17.7 97.5 196.0	8.0 44.2 89.1	15.0Ω/M' 49.2Ω/km	3.0Ω/M' 9.8Ω/km	.535 13.59	70	60%	35	115	63	207
<b>8325</b>		NEC: CMG CEC: CMG FT4	25	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	23.1 126.0 246.0	10.5 57.4 112.1	15.0Ω/M' 49.2Ω/km	2.9Ω/M' 9.5Ω/km	.620 15.75	70	60%	35	115	63	207	

DCR = DC Resistance • TC = Tinned Copper

\*Capacitance between conductors.

\*\*Capacitance between one conductor and other conductors connected to shield.