

Select Your Country/Region

Search

HomeProductsSupportServicesSelectorsHow to Buy

NetShelter VX 42U Enclosure w/out Sides Black

Rack enclosures with advanced cooling, power distribution, and cable management for server and networking applications in IT environments.

Includes: Baying kit, Casters, Doors, Key(s), Leveling feet, Roof, User Manual

Part Number: AR2101BLK

InfraStruXure

□ Physical

Compare Models

<u>■ Email Technical Specifications</u>

Printer Friendly

Additional Information

Product Overview
User Manual & Installation Guides
Submittal Drawings
Product Distribution



[+] More Images

Technical Specifications

Net Weight	282.00 lbs. (128.18 kg)
Maximum Height	81.50 inches (2070 mm)
Maximum Width	23.00 inches (584 mm)
Maximum depth	42.20 inches (1072 mm)
Shipping Weight	320.00 lbs. (145.45 kg)
Shipping Height	87.00 inches (2210 mm)
Shipping Width	29.50 inches (749 mm)
Shipping Depth	47.50 inches (1207 mm)
Weight Capacity (static load)	2000.00 lbs. (909.09 kg)
Weight Capacity (dynamic load)	2000.00 lbs. (909.09 kg)
Rack Height	42U
Color	Black
Units per Pallet	1.00
Vertical Posts	16 gauge
Front Door	16 gauge
Rear Door	16 gauge
Roof	18 gauge
EIA Mounting Rails	14 gauge

Options:

- AC Connections
- o <u>Services</u>

Features:

- O Adjustable mounting depth
- O Guaranteed Compatability
- Lockable Doors
- O Multi-vendor equipment compatibility
- O Numbered U positions
- Optimized depth
- O Optimized width
- Powder coat paint finish
- O Protective grounding provisions
- O Quick release doors
- O Rear Cable Management channels
- O Reversible doors
- O Rolls through a 7 foot doorway
- O Roof and base cable access
- O Ships fully assembled
- O Split rear doors
- O UBC Zone 4 stabilization provisions



Standard Warranty	
Standards	EIA-310-D
Protection Class	IP 20

Copyright © American Power Conversion Corp., all rights reserved About APCInvestorsJob SeekersPressFeedbackContactPrivacy Policy