

Home
Product Information
Literature & Price Lists
Distributors
Investor Information
About Us
Contact Us

Quick Menu:

- DXF Downloads
- New Products
- Hammond News

Oil Tight Hole Plugs



- Designed to seal unused pushbutton holes, conduit openings and knockout holes against dust, oil and water.
- Standard Pushbutton size is 30.5mm

Steel Hole Plugs

- Available in 12 sizes.
- Finished in gray.
- Oil resistant gasket.
- Secured with an 8-32 x 3/4" threaded stud and plated wing nut.

Part No.	Description	Diameter
HP22	22mm Pushbutton	1.22
HP50	0.5" Conduit	1.38
HP75	0.75" Conduit	1.63
HPB	Std. Pushbutton	1.75
HP100	1" Conduit	1.88
HP125	1.25" Conduit	2.25
HP150	1.5" Conduit	2.50
HP200	2" Conduit	3.00
HP250	2.5" Conduit	2.50
HP300	3" Conduit	4.14
HP350	3.5" Conduit	4.66
HP400	4" Conduit	5.19

Stainless Steel Hole Plugs

- Available in 8 sizes.
- Finished in brushed natural stainless Finish.
- Oil resistant gasket.
- Secured with an 8-32 x 3/4" threaded stud and plated wing nut.

Part No.	Description	Diameter
HP22SS	22mm Pushbutton	1.22
HP50SS	0.5" Conduit	1.38
HP75SS	0.75" Conduit	1.63
HPBSS	Std. Pushbutton	1.75
HP100SS	1" Conduit	1.88
HP125SS	1.25" Conduit	2.25
HP150SS	1.5" Conduit	2.50
HP200SS	2" Conduit	3.00