

1. Base Data

Part No. 300-73110

Type TCN20-38.1/19.1

Color Black (BK)

Features TCN20 is a general purpose, flame-retardant polyolefin tubing with good resistance to common fluids and solvents. This flexible, 2:1 shrink ration tubing has an excellent physical and electrical performance. The low shrink temperature and the mechanical strength make this tubing being widely used in the electrical, electronics and automotive industry.

Application TCN20 is suitable for a wide range of applications like electrical insulations, mechanical protection, cable bundling, et cetera.

shortdescription50character Black thin wall heat shrink tubing

Shrink Ratio 2:1

Size 38,1/19,1

Variant Thin-Wall

2. Product Dimensions

Length (L) 30 m

Wall Thickness (WT) .04

Wall Thickness 1.02 mm

Longitudinal change after shrinkage +/- 5%

Recov. Ø d max. 19.1 mm

Recovered Ø .75 "

Supplied Ø 1.5 " / 38.1 mm

4. Material and Specifications

Material	Polyolefin, cross-linked (POX)
Material Shortcut	POX
Certification	UL224 125 °C 600V VW-1
Dielectric Strength	20 kV/mm according to IEC 243
Flammability	self-extinguishing
Insulation Class	E (VDE 0530)
Min. Shrink Temperature	+100 °C
Operating Temperature	-67 °F to +257 °F (-55 °C to +125 °C)
ROHS Conformity	