

## MBT20S-S

Stainless Steel Tie, 150lb Length 20.5" Max Bun Dia 6" SS304, Metal, 100/pk

Article Number: 111-93208

Part Number: MBT20S-S

Type: MBT20SS

Material: SS304



### 1. Base Data

---

**Part No.** MBT20S-S

**Type** MBT20SS

**Color** Metal

**Features** HellermannTyton's stainless steel ties are designed to secure hoses, cables, poles, pipes, and more when harsh environmental conditions may adversely affect the bundling application. Used where corrosion, vibration, weathering, radiation, and temperature

## Application

**304 Material** Grade 304 material is commonly used for stainless steel bundling applications and suits most general purpose requirements. It features the ability to withstand most environmental conditions, particularly in applications where vib

<b>Label E-Number Finland</b>	13 703 20
-------------------------------	-----------

## 2. Product Dimensions

---



<b>Min. Tensile Strength</b>	150 lbs / 670 N
------------------------------	-----------------

<b>Length (L)</b>	20.5 " / 521 mm
-------------------	-----------------

<b>Width (W)</b>	.18 " / 4.6 mm
------------------	----------------

<b>Min. Ø Bundle</b>	.59 " / 15.0 mm
----------------------	-----------------

<b>Max. Ø Bundle</b>	6 " / 152 mm
----------------------	--------------

## 4. Material and Specifications

---

<b>Material</b>	Stainless Steel Type SS304 (SS304)
-----------------	------------------------------------

<b>Material Shortcut</b>	SS304
--------------------------	-------

<b>Operating Temperature</b>	-112 °F to +1000 °F (-80 °C to +538 °C)
------------------------------	---

## Logistic and Packaging

---

<b>Packaging Type</b>	bag
<b>Pkg. Qty.</b>	100
<b>Carton Qty.</b>	1 Pieces
<b>EAN code</b>	5022660170287
<b>UPC</b>	08930620319

### Stainless Steel Cable Ties

HellermannTyton's stainless steel ties are designed to secure hoses, cables, poles, pipes, and more when harsh environmental conditions may adversely affect the bundling application. Used where corrosion, vibration, weathering, radiation, and temperature extremes are a concern, HellermannTyton's stainless steel ties can be used in virtually any indoor, outdoor, and underground application.

### MK9SST Stainless Steel Cable Tie Installation Tool

Product Selection					
Article No.	Part No.	Type	Description	Cable Tie Series	Pkg. Qty.
110-95000	<b>MK9SST</b>	MK9SST	Adapted for use with stainless steel ties, the MK9 Stainless Steel tool retains the same design features as the MK9 series. The MK9SST accommodates all HellermannTyton stainless steel ties. Comes standard with padded foam grips for comfort and control and a hook for hanging on a belt or tether.	All MBT Series for both 304 and 316 materials	1


#### 304 Material

Grade 304 material is commonly used for stainless steel bundling applications and suits most general purpose requirements. It features the ability to withstand most environmental conditions, particularly in applications where vibration, general weathering, radiation and temperature extremes are a concern.

- Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool
- Fully enclosed head does not allow dirt or grit to interfere with locking mechanism
- High tensile strength option for added strength and safety on heavy duty applications



HellermannTyton's MK9SST tool is durable and lightweight, offering superior stainless steel cable tie installation.



Material Data	
Material	<b>Stainless Steel Type SS304 (SS304)</b>
Operating Temperature	<b>-112 °F to +1000 °F (-80 °C to +538 °C)</b>



Product Selection											
Article No.	Part No.	Type	Min. Tensile Strength		Length (L)		Max. Ø Bundle		Width (W)		
			lbs.	(N)	in.	(mm)	in.	(mm)	in.	(mm)	Pkg. Qty.
<b>150 lb. Stainless Steel Ties</b>											
111-93058	<b>MBT5S-S</b>	MBT5SS	150 lbs	(670)	5.0"	(127)	1"	(25)	.18"	(4.6)	100
111-93088	<b>MBT8S-S</b>	MBT8SS	150 lbs	(670)	7.9"	(201)	2"	(50)	.18"	(4.6)	100
111-93148	<b>MBT14S-S</b>	MBT14SS	150 lbs	(670)	14.3"	(362)	4"	(102)	.18"	(4.6)	100
111-93208	<b>MBT20S-S</b>	MBT20SS	150 lbs	(670)	20.5"	(521)	6"	(152)	.18"	(4.6)	100
111-93278	<b>MBT27S-S</b>	MBT27SS	150 lbs	(670)	26.8"	(681)	8"	(203)	.18"	(4.6)	100
111-93338	<b>MBT33S-S</b>	MBT33SS	150 lbs	(670)	33"	(838)	10"	(254)	.18"	(4.6)	100
<b>250 lb. Stainless Steel Ties</b>											
111-94088	<b>MBT8H-S</b>	MBT8HS	250 lbs	(1115)	7.9"	(201)	2"	(50)	.31"	(7.9)	50
111-94148	<b>MBT14H-S</b>	MBT14HS	250 lbs	(1115)	14.3"	(362)	4"	(102)	.31"	(7.9)	50
111-94208	<b>MBT20H-S</b>	MBT20HS	250 lbs	(1115)	20.5"	(521)	6"	(152)	.31"	(7.9)	50
111-94278	<b>MBT27H-S</b>	MBT27HS	250 lbs	(1115)	26.8"	(681)	8"	(203)	.31"	(7.9)	50
111-94338	<b>MBT33H-S</b>	MBT33HS	250 lbs	(1115)	33"	(838)	10"	(254)	.31"	(7.9)	50

Installation tools for the above cable ties - MK9SST. Dimensions are approximate and subject to technical changes. Use **Part No.** for ordering and **Type** for specification purposes. Stainless steel ties and materials should be tested thoroughly under end use conditions to determine suitability for the application.