

## RT40R9C2

Releasable Cable Tie, 40lb. 8.46" Max. Bun. Dia 2.0" PA66, Natural, 100/pk

Article Number: 115-06219

Part Number: RT40R9C2

Type: RT40R

Material: PA66



### 1. Base Data

---

<b>Part No.</b>	RT40R9C2
<b>Type</b>	RT40R
<b>Color</b>	Natural
<b>Features</b>	The extended pawl allows for simple and quick release of the ties.
<b>Application</b>	Perfect for prototype construction and service requiring the addition of wire on existing harnesses.


## 2. Product Dimensions

---

Min. Tensile Strength	40 lbs / 180 N
Length (L)	8.46 " / 215 mm
Width (W)	.16 " / 4.0 mm
Min. Ø Bundle	.06 " / 1.5 mm
Max. Ø Bundle	2.0 " / 51.0 mm

## 4. Material and Specifications

---

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
ROHS Conformity	

## Logistic and Packaging

---

Packaging Type	bag
Pkg. Qty.	100
Carton Qty.	1 Pieces
EAN code	4031026108407
UPC	08930604426

**Miscellaneous**


---

**UL Recognized (US and Canada)** Yes

## Releasable Ties

The extended pawl allows for simple and quick release of the ties. Perfect for prototype construction and service requiring the addition of wires on existing harnesses.

Material Data	
Material	<b>Polyamide 6.6 (PA66)</b>
Operating Temperature	<b>-40 °F to +185 °F (-40 °C to +85 °C) continuous</b>
Flammability	<b>UL94 V2</b>



RT40R



RT50S and RT50LL



Product Selection			Min. Tensile Strength	Length (L)	Max. Ø Bundle	Width (W)	Color	Pkg. Qty.
Article No.	Part No.	Type						
<b>RT40R</b>								
115-06219	<b>RT40R9C2</b>	RT40R	34 lbs (150)	8.46" (215)	2.0" (51)	.16" (4.0)	Natural	100
115-06204	<b>RT40R9M4</b>	RT40R	34 lbs (150)	8.46" (215)	2.0" (51)	.16" (4.0)		1000
115-06200	<b>RT40R0C2</b>	RT40R	34 lbs (150)	8.46" (215)	2.0" (51)	.16" (4.0)	Black	100
115-06202	<b>RT40R0M4</b>	RT40R	34 lbs (150)	8.46" (215)	2.0" (51)	.16" (4.0)		1000
<b>RT50S</b>								
115-06319	<b>RT50S9C2</b>	RT50S	50 lbs (225)	6.5" (165)	1.38" (35)	.18" (4.6)	Natural	100
115-06304	<b>RT50S9M4</b>	RT50S	50 lbs (225)	6.5" (165)	1.38" (35)	.18" (4.6)		1000
115-06300	<b>RT50S0C2</b>	RT50S	50 lbs (225)	6.5" (165)	1.38" (35)	.18" (4.6)	Black	100
115-00035	<b>RT50S0M4</b>	RT50S	50 lbs (225)	6.5" (165)	1.38" (35)	.18" (4.6)		1000
<b>RT50LL</b>								
115-06102	<b>RT50LL9C2</b>	RT50LL	50 lbs (225)	15" (380)	3.98" (101)	.18" (4.6)	Natural	100
115-06104	<b>RT50LL9M4</b>	RT50LL	50 lbs (225)	15" (380)	3.98" (101)	.18" (4.6)		1000
115-00039	<b>RT50LL0C2</b>	RT50LL	50 lbs (225)	15" (380)	3.98" (101)	.18" (4.6)	Black	100
115-06101	<b>RT50LL0M4</b>	RT50LL	50 lbs (225)	15" (380)	3.98" (101)	.18" (4.6)		1000

Dimensions are approximate and subject to technical changes. Use **Part No.** for ordering and **Type** for specification purposes.