

T50MR0M4

Screw Mount Tie, 50lb. 8.46" Max Bun Dia 1.77" #10 Screw PA66, Black, 1000/pk

Article Number: 113-05002

Part Number: T50MR0M4

Type: T50MR

Material: PA66



1. Base Data


| | |
|--------------------|---|
| Part No. | T50MR0M4 |
| Type | T50MR |
| Color | Black (BK) |
| Features | One-piece, all plastic ties for quick, simple cable mounting. |
| Application | The 'T' range of cable ties have a built in mounting hole and once fastened around the cables the bundle can be simply secured to the panel with a screw or bolt. |

2. Product Dimensions



| | |
|------------------------------|------------------|
| Min. Tensile Strength | 50 lbs / 225 N |
| Length (L) | 8.46 " / 215 mm |
| Width (W) | .18 " / 4.7 mm |
| Height (H) | .22 " / 5.7 mm |
| Min. Ø Bundle | .06 " / 1.5 mm |
| Max. Ø Bundle | 1.77 " / 45.0 mm |
| Mounting Hole Ø | .21 " / 5.4 |

4. Material and Specifications

| | |
|------------------------------|---|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) continuous |
| ROHS Conformity |  |

Logistic and Packaging

| | |
|-----------------------|-------------|
| Packaging Type | bag |
| Pkg. Qty. | 1000 |
| Carton Qty. | 5000 |
| UPC | 08930608589 |


Miscellaneous

UL Recognized (US and Canada) Yes

Screw Mount Ties

One-piece, all plastic ties for quick, simple cable mounting.

| Material Data | |
|-----------------------|--|
| Material | Polyamide 6.6 (PA66) |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) continuous |
| Flammability | UL94 V2 |



| Product Selection | | | | Min. Tensile Strength lbs. (N) | Length (L) in. (mm) | Max. Ø Bundle in. (mm) | Width (W) in. (mm) | Color | Pkg. Qty. | |
|-------------------|------------------|--------|----------------------|-----------------------------------|------------------------|---------------------------|-----------------------|---------|-----------|--|
| Article No. | Part No. | Type | Mounting | | | | | | | |
| T18MR | | | | | | | | | | |
| 113-00026 | T18MR9C2 | T18MR | # 4 screw | 18 lbs (80) | 4.33" (110) | .79" (20) | .10" (2.5) | Natural | 100 | |
| 113-00028 | T18MR9M4 | T18MR | | 18 lbs (80) | 4.33" (110) | .79" (20) | .10" (2.5) | Natural | 1000 | |
| 113-00022 | T18MR0C2 | T18MR | | 18 lbs (80) | 4.33" (110) | .79" (20) | .10" (2.5) | Black | 100 | |
| 113-00024 | T18MR0M4 | T18MR | | 18 lbs (80) | 4.33" (110) | .79" (20) | .10" (2.5) | Black | 1000 | |
| T30MR | | | | | | | | | | |
| 113-03019 | T30MR9C2 | T30MR | # 8 screw | 30 lbs (135) | 6.30" (160) | 1.26" (32) | .14" (3.5) | Natural | 100 | |
| 113-00036 | T30MR9M4 | T30MR | | 30 lbs (135) | 6.30" (160) | 1.26" (32) | .14" (3.5) | Natural | 1000 | |
| 113-03010 | T30MR0C2 | T30MR | | 30 lbs (135) | 6.30" (160) | 1.26" (32) | .14" (3.5) | Black | 100 | |
| 113-03011 | T30MR0M4 | T30MR | | 30 lbs (135) | 6.30" (160) | 1.26" (32) | .14" (3.5) | Black | 1000 | |
| T50MR | | | | | | | | | | |
| 113-05004 | T50MR9C2 | T50MR | # 10 screw | 48 lbs (215) | 8.46" (215) | 1.77" (45) | .18" (4.6) | Natural | 100 | |
| 113-05007 | T50MR9M4 | T50MR | | 48 lbs (215) | 8.46" (215) | 1.77" (45) | .18" (4.6) | Natural | 1000 | |
| 113-05000 | T50MR0C2 | T50MR | | 48 lbs (215) | 8.46" (215) | 1.77" (45) | .18" (4.6) | Black | 100 | |
| 113-05002 | T50MR0M4 | T50MR | | 48 lbs (215) | 8.46" (215) | 1.77" (45) | .18" (4.6) | Black | 1000 | |
| T50MRT | | | | | | | | | | |
| 113-05101 | T50MRT9C2 | T50MRT | #6-32 tap thru screw | 50 lbs (225) | 8.47" (215) | 1.77" (45) | .19" (4.7) | Natural | 100 | |
| 113-05102 | T50MRT9M4 | T50MRT | | 50 lbs (225) | 8.47" (215) | 1.77" (45) | .19" (4.7) | Natural | 1000 | |
| 113-05100 | T50MRT0C2 | T50MRT | | 50 lbs (225) | 8.47" (215) | 1.77" (45) | .19" (4.7) | Black | 100 | |
| 113-00037 | T50MRT0M4 | T50MRT | | 50 lbs (225) | 8.47" (215) | 1.77" (45) | .19" (4.7) | Black | 1000 | |
| T50MI | | | | | | | | | | |
| 113-00032 | T50MI9C2 | T50MI | # 10 screw | 50 lbs (225) | 12.40" (315) | 3.35" (85) | .19" (4.7) | Natural | 100 | |
| 113-00033 | T50MI9M4 | T50MI | | 50 lbs (225) | 12.40" (315) | 3.35" (85) | .19" (4.7) | Natural | 1000 | |
| 113-00038 | T50MI0C2 | T50MI | | 50 lbs (225) | 12.40" (315) | 3.35" (85) | .19" (4.7) | Black | 100 | |
| 113-00031 | T50MI0M4 | T50MI | | 50 lbs (225) | 12.40" (315) | 3.35" (85) | .19" (4.7) | Black | 1000 | |
| T50ML | | | | | | | | | | |
| 113-05419 | T50ML9C2 | T50ML | # 10 screw | 50 lbs (225) | 15.35" (390) | 4.00" (100) | .18" (4.6) | Natural | 100 | |
| 113-05403 | T50ML9M4 | T50ML | | 50 lbs (225) | 15.35" (390) | 4.00" (100) | .18" (4.6) | Natural | 1000 | |
| 113-00007 | T50ML0C2 | T50ML | | 50 lbs (225) | 15.35" (390) | 4.00" (100) | .18" (4.6) | Black | 100 | |
| 113-00035 | T50ML0M4 | T50ML | | 50 lbs (225) | 15.35" (390) | 4.00" (100) | .18" (4.6) | Black | 1000 | |
| T120MR | | | | | | | | | | |
| 113-12029 | T120MR9K2 | T120MR | # 1/4" screw | 120 lbs (535) | 15.55" (395) | 4.02" (102) | .30" (7.6) | Natural | 50 | |
| 113-00018 | T120MR9H4 | T120MR | | 120 lbs (535) | 15.55" (395) | 4.02" (102) | .30" (7.6) | Natural | 500 | |
| 113-12020 | T120MR0K2 | T120MR | | 120 lbs (535) | 15.55" (395) | 4.02" (102) | .30" (7.6) | Black | 50 | |
| 113-00011 | T120MR0H4 | T120MR | | 120 lbs (535) | 15.55" (395) | 4.02" (102) | .30" (7.6) | Black | 500 | |

Installation tools - MK7, MK7HT, MK7P, MK9, MK9HT, MK9P. Dimensions are approximate and subject to technical changes. Use **Part No.** for ordering and **Type** for specification purposes.