



## MACH102-8TP-F

Industrial Networking:Industrial Ethernet:MACH100:Switches

### Delivery informations

|                     |            |
|---------------------|------------|
| Availability        | available  |
| Document created at | 22.05.2009 |

### Product description

|             |  |
|-------------|--|
| Description | 10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design |
|-------------|--|

|                        |  |
|------------------------|--|
| Port type and quantity | 10 ports in total; 8x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports |
|------------------------|--|

|      |               |
|------|---------------|
| Type | MACH102-8TP-F |
|------|---------------|

|           |             |
|-----------|-------------|
| Order No. | 943 969-201 |
|-----------|-------------|

### More Interfaces

|                                |   |
|--------------------------------|---|
| Power supply/signaling contact | 1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC) |
|--------------------------------|---|

|                |  |
|----------------|--|
| V.24 interface | 1 x RJ11 socket, serial interface for device configuration |
|----------------|--|

|               |   |
|---------------|---|
| USB interface | 1 x to connect auto-configuration adapter ACA21-USB |
|---------------|---|

### Network size - length of cable

|                   |          |
|-------------------|----------|
| Twisted pair (TP) | 0 - 100m |
|-------------------|----------|

|                                |  |
|--------------------------------|--|
| Multimode fiber (MM) 50/125 µm | Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC |
|--------------------------------|--|

|                                  |  |
|----------------------------------|--|
| Multimode fiber (MM) 62.5/125 µm | Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC |
|----------------------------------|--|

|                                |  |
|--------------------------------|--|
| Single mode fiber (SM)9/125 µm | Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC |
|--------------------------------|--|

|  |   |
|--|---|
| Single mode fiber (LH)9/125 µm (long haul transceiver) | Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC |
|--|---|

### Network size - cascadability

|                        |     |
|------------------------|-----|
| Line - / star topology | any |
|------------------------|-----|

|   |                                      |
|---|--------------------------------------|
| Ring structure (HIPER-Ring) quantity switches | 50 (reconfiguration time < 0,3 sec.) |
|---|--------------------------------------|

### Power requirements

|                   |                           |
|-------------------|---------------------------|
| Operating voltage | 100 - 240 VAC, 47 - 63 Hz |
|-------------------|---------------------------|

|                           |    |
|---------------------------|----|
| Power outputin Btu (IT) h | 41 |
|---------------------------|----|

|               |             |
|---------------|-------------|
| Rated current | 0.4 - 0.2 A |
|---------------|-------------|

|                   |      |
|-------------------|------|
| Power consumption | 12 W |
|-------------------|------|

### Software

|            |  |
|------------|--|
| Management | serial Interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP |
|------------|--|

|             |   |
|-------------|---|
| Diagnostics | LEDs, log-file, syslog, signal contact, RMON (statistic, history, alarms, events), port mirroring, topology discovery 802.1AB, cable diagnostic |
|-------------|---|

|               |  |
|---------------|--|
| Configuration | Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, auto-configuration adapter (ACD11, ACA21-USB), Watchdog configuration; integrated DHCP server |
|---------------|--|

|          |   |
|----------|---|
| Security | Port security (IP and MAC), SNMP V3, SSH, authentication (802.1x) |
|----------|---|

|                      |   |
|----------------------|---|
| Redundancy functions | HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, dual homing, link aggregation |
|----------------------|---|

|        |  |
|--------|--|
| Filter | QoS 4 Klassen, Portpriorisierung (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, Multicast (IGMP Snooping/Querier), Multicast Detection unknown Multicast, Broadcastlimiter, Fast Aging, Multicast GMRP IEEE 802.1D |
|--------|--|

|  |  |
|--|--|
| Industrial Profiles                        | EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix  |
| Realtime                                   | SNTP server, realtime clock with energy buffer   |
| Flow control                               | Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress   |
| <b>Ambient conditions</b>                  |  |
| Operating temperature                      | 0° - +50°C   |
| Storage/transport temperature              | -20° - +85°C   |
| Relative humidity (non-condensing)         | 10% to 95%   |
| MTBF                                       | 15.67 years (MIL-HDBK-217F Gb 25°C)  |
| <b>Mechanical construction</b>             |  |
| Dimensions (W x H x D)                     | 448 x 310 x 44 (without fixing bracket)  |
| Mounting                                   | 19" control cabinet  |
| Weight                                     | 3.60 kg  |
| Protection class                           | IP20   |
| <b>EMC interference immunity</b>           |  |
| EN 61000-4-2 electrostatic discharge (ESD) | 4 kV contact discharge, 8 kV air discharge   |
| EN 61000-4-3 electromagnetic field         | 10 V/m (80 - 2700 MHz)   |
| EN 61000-4-4 fast transients (burst)       | 2 kV power line, 4 kV data line  |
| EN 61000-4-5 surge voltage                 | power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line  |
| EN 61000-4-6 conducted immunity            | 10 V (150 kHz - 80 MHz)  |
| <b>EMC emitted immunity</b>                |  |
| FCC CFR47 Part 15                          | FCC 47 CFR Part 15 Class A   |
| EN 55022                                   | EN 55022 Class A   |
| <b>Approvals</b>                           |  |
| Safety of industrial control equipment     | cUL 508 (pending)  |
| <b>Scope of delivery and accessories</b>   |  |
| Scope of delivery                          | MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual |
| Accessories to order separately            | Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software  |