

Dials & Knobs



The CLAROSTAT POWER RESISTOR DECADE is the essential tool in electronic and electrical design, testing and repair...for controlling known or unknown resistances...selected or determined under active operational conditions.

It provides a power resistor of any required resistance from 1 to 999,999 ohms in 10hm increments. The ohmage is selected by six dials, and the value is read directly - in sequence - from the dials, simplifying the selection of known or unknown resistance for use in working circuits.

Style	Resistive Element	Power Rating (watts)	Resistive Range (ohms)	Tolerance
DECADE BOX				

240C

Table top	Wirewound	225 Max	1-999K	±2%, ±5%
-----------	-----------	---------	--------	----------

DIALS ■ DIGITAL READOUT



Series	Style	Number of Turns
DR300 DR400	1.75 inch long x 1 inch wide, brake lever, accepts 1/4" diameter shaft.	10 100

Series	Style	Housing	Brake Lever
DIALS ■ CONCENTRIC SCALE			




411		Black anodized	No
1411	10-turn,	Black plastic	No
412	1 inch dia.,	Black anodized	Yes
1412	accepts	Black plastic	Yes
461	1/4" dia.	Clear anodized	No
1461	shaft.	Gray plastic	No
462		Clear anodized	Yes
1462		Gray plastic	Yes

DIALS ■ CONCENTRIC SCALE/DIGITAL READOUT



Series	Style	Housing
316-11 316-12	10-turn, 7/8 inch diameter, brake lever, accepts 1/4" diameter shaft.	Clear anodized Black anodized

Style	Knob Diameter	Color	Shaft Diameter
HD			



HD	Saw-cut indicator	HD-50= .500" HD-75= .750" HD-90= .925"	1= clear 2= black 3= matte clear 4= matte black	5= .250" 6= .125"
JD	Straight knurl, top and side indicator	JD-50= .500" JD-75= .750" JD-90= .925"	1= clear 2= black 3= matte clear 4= matte black	5= .250" 6= .125"

Style	Knob Diameter	Color	Shaft Diameter
DD			



DD	Straight knurl, side indicator	DD-50= .500" DD-75= .750" DD-90= .925"	1= clear 2= black 3= matte clear 4= matte black	5= .250" 6= .125"
DDS	Skirted, arrowhead on skirt	DDS-50= .500" DDS-75= .750" DDS-90= .925"	1= clear 2= black 3= matte clear 4= matte black	5= .250" 6= .125"